

KT5011



Capacitive touch sensor

KTRDHOK-RBPKG/AM/AS/0,3M



Product characteristics

Electrical design	PNP
Output function	normally open
Dimensions [mm]	Ø 96.9 / L = 11

Application

Principle of operation	dynamic
------------------------	---------

Electrical data

Operating voltage [V]	12...30 DC
Current consumption [mA]	30
Protection class	III
Reverse polarity protection	yes
Max. power-on delay time [ms]	500

Outputs

Electrical design	PNP
Output function	normally open
Permanent current rating of switching output DC [mA]	200
Short-circuit protection	yes
Overload protection	yes
Length of output signal [ms]	300

Reaction times

Response time [ms]	35
--------------------	----

KT5011



Capacitive touch sensor

KTRDHOK-RBPKG/AM/AS/0,3M

Operating conditions

Ambient temperature	[°C]	-40...85
Protection		IP 67; IP 69K; (on the front)

Tests / approvals

MTTF	[years]	490.4
------	---------	-------

Mechanical data

Weight	[g]	114
Dimensions	[mm]	Ø 96.9 / L = 11
Material		actuating surface: PA Grilamid TR 90UV transparent; housing: PC/ABS black

Displays / operating elements

Display	Switching status	8 x LED, red
	Power	8 x LED, green

Accessories

Accessories (optional)	surround in different colors
------------------------	------------------------------

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection - plug

Cable: 0.3 m, PUR

Connector: 1 x M8; coding: A



Connection

