




Measurement insert for flow transmitters with fast response time

SBM34XKX10KG/O/US



Product characteristics		
Measuring range	[l/min]	0.3...25
Process connection	threaded connection G 3/4 external thread	
Application		
Media	Liquids; water; glycol solutions	
Medium temperature	[°C]	10...180
Pressure rating	15 bar	1.5 MPa
Note on pressure rating	at max. medium temperature	
	at temperatures up to 85 °C: 25 bar / 2,5 MPa	
Electrical data		
Operating voltage tolerance	[%]	-15...10
Operating voltage	[V]	24 DC; (to SELV/PELV)
Current consumption	[mA]	< 35
Protection class	III	
Reverse polarity protection	yes	

SBM613



Measurement insert for flow transmitters with fast response time

SBM34XKX10KG/O/US

Outputs		
Output signal		analog signal
Analog current output	[mA]	4...20
Max. load	[Ω]	500
Short-circuit protection		yes
Overload protection		yes
Measuring/setting range		
Measuring range	[l/min]	0.3...25
Accuracy / deviations		
Repeatability		1
	[% of the final value]	
Measuring error		± 5
	[% of the final value]	
Reaction times		
Response time	[s]	< 0.01
Operating conditions		
Ambient temperature	[°C]	0...60
Storage temperature	[°C]	-15...80
Protection		IP 65; IP 67
Tests / approvals		
EMC	DIN EN 61000-6-2	
	DIN EN 61000-6-3	
Shock resistance	DIN EN 60068-2-27	20 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	5 g (10...2000 Hz)
MTTF	[years]	1380
Mechanical data		
Weight	[g]	285
Housing		tubular
Dimensions	[mm]	Ø 35 / L = 121
Material		brass white bronze coated; PPS; copper alloy; aluminum anodized; silicone; PEI
Materials (wetted parts)		stainless steel (1.4401 / 316); brass; PPS; O-ring: FKM
Tightening torque	[Nm]	15
Process connection		threaded connection G 3/4 external thread
Switching cycles mechanical		10 million
Remarks		
Remarks		All data refer to water (20 °C).
		Recommendation Use 200 micron filtration
Pack quantity		1 pcs.

SBM613



Measurement insert for flow transmitters with fast response time

SBM34XKX10KG/O/US


Electrical connection - plug

Cable: 0.3 m, silicone

Connector: 1 x M12; coding: A



Connection



Colors to DIN EN 60947-5-2
Core colors :
BN = brown
BU = blue
WH = white

Diagrams and graphs

