


SBN234



Flow meter with fast response and display

SBN34IQ0FRKG

Please note the changed housing design!



Product characteristics		
Number of inputs and outputs	Number of digital outputs: 2; Number of analog outputs: 1	
Measuring range	10...600 gph	0.2...10 gpm
Process connection	threaded connection 3/4" NPT Internal thread	
Application		
System	gold-plated contacts	
Application	for industrial applications	
Media	Liquids; water; glycol solutions; Coolants	



Flow meter with fast response and display

SBN34IQ0FRKG

Note on media	oil 1 with viscosity: 10 mm²/s (104 °F)	
	oil 2 with viscosity: 46 mm²/s (104 °F)	
Medium temperature [°F]	14...212	
Pressure rating	40 bar	4 MPa
MAWP (for applications according to CRN) [bar]	40	
Electrical data		
Operating voltage [V]	18...30 DC; (to SELV/PELV)	
Current consumption [mA]	< 50	
Protection class	III	
Reverse polarity protection	yes	
Power-on delay time [s]	< 3	
Inputs / outputs		
Number of inputs and outputs	Number of digital outputs: 2; Number of analog outputs: 1	
Outputs		
Total number of outputs	2	
Output signal	switching signal; analog signal; frequency signal; IO-Link; (configurable)	
Number of digital outputs	2	
Output function	normally open / closed; (configurable)	
Max. voltage drop switching output DC [V]	2	
Permanent current rating of switching output DC [mA]	150; (per output 2 x 200 (...140 °F); 2 x 250 (...104 °F))	
Switching cycles (mechanical)	10 million	
Number of analog outputs	1	
Analog current output [mA]	4...20	
Max. load [Ω]	500	
Short-circuit protection	yes	
Overload protection	yes	
Frequency of the output [Hz]	0...10000	
Measuring/setting range		
Measuring range	10...600 gph	0.2...10 gpm
Display range	0...720 gph	0...12 gpm
Resolution	5 gph	0.1 gpm
Set point SP	5...600 gph	0.1...10 gpm
Reset point rP	0...595 gph	0...9.9 gpm
Frequency end point, FEP	40...600 gph	0.67...10 gpm
In steps of	5 gph	0.1 gpm
Frequency at the end point FRP [Hz]	10...10000	
Measuring dynamics	1:50	
Temperature monitoring		
Measuring range [°F]	14...212	
Display range [°F]	-26...252	
Resolution [°F]	2	



Flow meter with fast response and display

SBN34IQ0FRKG

Set point SP	[°F]	16...212
In steps of	[°F]	2
Frequency start point, FSP	[°F]	14...172
Frequency end point, FEP	[°F]	54...212
Frequency at the end point FRP	[Hz]	10...10000

Accuracy / deviations

Flow monitoring

Accuracy (in the measuring range)	± (4 % MW + 1 % MEW); (Q > 1 l/min; medium and operating temperature: +71,6 °F ± 4K)
Repeatability	± 1 % MEW

Temperature monitoring

Temperature drift	0,9802 °F / K
Accuracy	[K] 3 K (77 °F; Q > 1 l/min)

Reaction times

Flow monitoring

Response time	[s] 0.01
Damping process value dAP	[s] 0...5
Damping for the analog output dAA	[s] 0...5

Temperature monitoring

Dynamic response T05 / T09	[s] T09 = 120 (Q > 1 l/min)
----------------------------	-----------------------------

Software / programming

Parameter setting options	hysteresis / window; normally open / closed; switching logic; current output; medium selection; damping for the switching output / analog output; display can be rotated and switched off; standard unit of measurement; process value color
---------------------------	--

Interfaces

Communication interface	IO-Link				
Transmission type	COM2 (38,4 kBaud)				
IO-Link revision	1.1				
SDCI standard	IEC 61131-9 CDV				
Profiles	Smart Sensor: Process Data Variable; Device Identification				
SIO mode	yes				
Required master port class	A				
Process data analog	2				
Process data binary	2				
Min. process cycle time	[ms] 5				
Supported DeviceIDs	<table> <tr> <th>Type of operation</th><th>DeviceID</th></tr> <tr> <td>default</td><td>567</td></tr> </table>	Type of operation	DeviceID	default	567
Type of operation	DeviceID				
default	567				

Operating conditions

Ambient temperature	[°F] 32...140
Note on ambient temperature	medium temperature < 176 °F medium temperature < 212 °F: 32...104 °F
Storage temperature	[°F] 5...176
Protection	IP 65; IP 67



Flow meter with fast response and display

SBN34IQ0FRKG

Tests / approvals		
EMC	DIN EN 61000-6-2	
	DIN EN 61000-6-3	
Shock resistance	DIN EN 60068-2-27	20 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	5 g (10...2000 Hz)
MTTF [years]	145	
UL approval	UL approval number	I005
Pressure equipment directive	sound engineering practice; can be used for group 2 fluids; group 1 fluids on request	
Mechanical data		
Weight [g]	693	
Material	stainless steel (1.4404 / 316L); PBT+PC-GF30; PBT-GF20; PC; brass chemically nickel-plated	
Materials (wetted parts)	stainless steel (1.4401 / 316); stainless steel (1.4404 / 316L); brass (2.0371); brass chemically nickel-plated; PPS; O-ring: FKM	
Process connection	threaded connection 3/4" NPT Internal thread	
Displays / operating elements		
Display	Display unit	3 x LED, green
	Switching status	2 x LED, yellow
	Measured values	alphanumeric display, red/green 4-digit
	Programming	alphanumeric display, 4-digit
Remarks		
Remarks	Use of 200 micron filtration is recommended.	
	All data refer to water (68 °F).	
	MW = Measured value	
	MEW = Final value of the measuring range	
Notes	Please note the changed housing design!	
Pack quantity	1 pcs.	
Electrical connection		
Connector: 1 x M12; coding: A; Contacts: gold-plated		
		






Flow meter with fast response and display

SBN34IQ0FRKG

Connection



- OUT1:
- Switching output Volumetric flow quantity monitoring
 - Switching output Temperature monitoring
 - Frequency output Volumetric flow quantity monitoring
 - Frequency output Temperature monitoring
 - IO-Link


- OUT2:
- Switching output Volumetric flow quantity monitoring
 - Switching output Temperature monitoring
 - analog output Volumetric flow quantity monitoring
 - analog output Temperature monitoring
- Colors to DIN EN 60947-5-2

Core colors :

- BK = black
BN = brown
BU = blue
WH = white

Diagrams and graphs

Pressure loss



dP Pressure loss
Q volumetric flow quantity