


SV3050



Vortex flow meter

SVM12XXD0KG/US-100



Product characteristics

Number of inputs and outputs	Number of analog outputs: 1	
Measuring range	0.5...10 l/min	0.074...1.474 m/s
Process connection	threaded connection G 1/2 external thread DN6	

Application

System	gold-plated contacts	
Application	for industrial applications	
Installation	connection to pipe by means of an adapter	
Media	water; glycol solutions; Coolants	
Medium temperature [°C]	-40...100	
Min. bursting pressure	25 bar	2.5 MPa
Pressure rating	12 bar	1.2 MPa
Note on pressure rating	up to 40 °C	

Electrical data

Operating voltage [V]	8...33 DC	
Min. insulation resistance [MΩ]	100; (500 V DC)	
Protection class	III	
Power-on delay time [s]	< 2	
Measuring principle	Vortex	

Inputs / outputs

Number of inputs and outputs	Number of analog outputs: 1
------------------------------	-----------------------------

Outputs

Total number of outputs	1
-------------------------	---



Vortex flow meter

SVM12XXD0KG/US-100

Output signal	analog signal	
Number of analog outputs	1	
Analog current output	[mA]	4...20; (Q [l/min] = 0,625 x (I - 4 mA))
Max. load	[Ω]	< (Ub - 8 V) / 20 mA; Ub = 24 V: 800
Measuring/setting range		
Measuring range	0.5...10 l/min	0.074...1.474 m/s
Accuracy / deviations		
Flow monitoring		
Accuracy (in the measuring range)	Q < 50 % MEW: < 1 % MEW / Q > 50 % MEW: < 2 % MW; (water)	
Repeatability	0,2; (% of the final value)	
Reaction times		
Flow monitoring		
Response time	[s]	0.5
Operating conditions		
Ambient temperature	[°C]	-15...85
Storage temperature	[°C]	-30...85
Protection	IP 65	
Cavitation	P(absolute) discharge / P(difference) > 5.5 to avoid cavitation	
Tests / approvals		
EMC	EN 61326-2-3	
Shock resistance	DIN EN 60068-2-27	30 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	with water / 10...61 Hz 1 mm
		with water / 61...2000 Hz 2 g
MTTF	[years]	380
Pressure equipment directive	sound engineering practice; can be used for group 2 fluids; group 1 fluids on request	
Mechanical data		
Weight	[g]	67
Housing	rectangular	
Dimensions	[mm]	77 x 30.22 x 53
Material	PA 6T	
Materials (wetted parts)	ETFE; PA 6T; FKM	
Tightening torque	[Nm]	12
Process connection	threaded connection G 1/2 external thread DN6	
Displays / operating elements		
Display		Color display 1,44", 128 x 128 pixels
		2 x LED, yellow
Remarks		
Remarks	MW = Measured value	
	MEW = Final value of the measuring range	
Pack quantity	1 pcs.	

SV3050



Vortex flow meter

SVM12XXD0KG/US-100

Electrical connection

Connector: 1 x M12; coding: A; Contacts: gold-plated




Connection



OUT: analog output
Colors to DIN EN 60947-5-2
Core colors :
BN = brown
WH = white

Diagrams and graphs

Pressure loss



dP Pressure loss
Q volumetric flow quantity


SV3050



Vortex flow meter

SVM12XXD0KG/US-100

Minimum lifetime 10 years
referred to flow and high medium
temperatures



pressure rating (bar)

