


SV5614



SV vortex flowmeters with display for water based media

SVN12XXX50KG/US-100



1 1/2" NPT
DN 10



Product characteristics

Number of inputs and outputs	Number of analog outputs: 2	
Measuring range	32...634 gph	0.55...10.55 gpm
Process connection	threaded connection 1/2" NPT Internal thread DN10	

Application

System	gold-plated contacts
Application	for industrial applications
Media	water; glycol solutions; Coolants
Medium temperature [°F]	14...194

SV5614



SV vortex flowmeters with display for water based media

SVN12XXX50KG/US-100

Pressure rating	12 bar	174 psi	1.2 MPa
Note on pressure rating	up to 40 °C		
MAWP (for applications according to CRN) [bar]	4.8		
Electrical data			
Operating voltage [V]	18...30 DC		
Current consumption [mA]	< 30		
Min. insulation resistance [MΩ]	100; (500 V DC)		
Protection class	III		
Reverse polarity protection	yes		
Power-on delay time [s]	< 3		
Measuring principle	Vortex		
Inputs / outputs			
Number of inputs and outputs	Number of analog outputs: 2		
Outputs			
Total number of outputs	2		
Output signal	analog signal		
Number of analog outputs	2		
Analog current output [mA]	4...20		
Max. load [Ω]	500		
Short-circuit protection	yes		
Overload protection	yes		
Measuring/setting range			
Measuring range	32...634 gph	0.55...10.55 gpm	
Display range	0...760 gph	0...12.7 gpm	
Resolution	2 gph	0.05 gpm	
Analog start point ASP	0...508 gph	0...8.45 gpm	
Analog end point AEP	126...634 gph	2.1...10.55 gpm	
In steps of	2 gph	0.05 gpm	
Measuring dynamics	1:20		
Temperature monitoring			
Measuring range [°F]	14...194		
Display range [°F]	-22...230		
Resolution [°F]	1		
Analog start point [°F]	14...158		
Analog end point [°F]	50...194		
In steps of [°F]	1		
Accuracy / deviations			
Flow monitoring			
Accuracy (in the measuring range)	± 2 % MEW; (water)		
Repeatability	± 0,5 % MEW		
Temperature monitoring			
Accuracy [K]	± 1		



SV vortex flowmeters with display for water based media

SVN12XX50KG/US-100

Reaction times		
Flow monitoring		
Response time	[s]	1; (dAP = 0)
Damping process value dAP	[s]	0...5
Temperature monitoring		
Dynamic response T05 / T09	[s]	T09 = 6
Software / programming		
Parameter setting options	Damping for the analog output dAA; Display unit	
Operating conditions		
Ambient temperature	[°F]	32...140
Note on ambient temperature		medium temperature < 176 °F
		medium temperature < 194 °F: 32...122 °F
Storage temperature	[°F]	-4...176
Protection	IP 65; IP 67	
Tests / approvals		
EMC	DIN EN 61000-6-2	
	DIN EN 61000-6-3	
Shock resistance	DIN EN 60068-2-27	5 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	with water / 10...50 Hz 1 mm
		with water / 50...2000 Hz 2 g
MTTF	[years]	342
UL approval	UL approval number	I002
Pressure equipment directive	sound engineering practice; can be used for group 2 fluids; group 1 fluids on request	
Mechanical data		
Weight	[g]	466
Housing	rectangular	
Dimensions	[mm]	119 x 45 x 72
Material	stainless steel (1.4404 / 316L); PC; PBT+PC-GF30; PPS; TPE-U	
Materials (wetted parts)	stainless steel (1.4404 / 316L); ETFE; PA 6T; PPS; FKM	
Tightening torque	[Nm]	30
Process connection	threaded connection 1/2" NPT Internal thread DN10	
Displays / operating elements		
Display		Color display 1,44", 128 x 128 pixels
		2 x LED, yellow
Remarks		
Remarks	MW = Measured value	
	MEW = Final value of the measuring range	
Pack quantity	1 pcs.	

SV5614



SV vortex flowmeters with display for water based media


SVN12XXX50KG/US-100

Electrical connection

Connector: 1 x M12; coding: A; Contacts: gold-plated




Connection



OUT1: analog output Temperature monitoring
OUT2: analog output Volumetric flow quantity monitoring
Colors to DIN EN 60947-5-2
Core colors :
BK = black
BN = brown
BU = blue
WH = white

Diagrams and graphs

pressure rating (bar)




SV5614



SV vortex flowmeters with display for water based media

SVN12XXX50KG/US-100

Pressure loss



dP Pressure loss
Q volumetric flow quantity