

## Inductive sensor

IG-3005-BPKG



## Product characteristics

|                    |                  |
|--------------------|------------------|
| Electrical design  | PNP              |
| Output function    | normally open    |
| Sensing range [mm] | 5                |
| Housing            | Threaded type    |
| Dimensions [mm]    | M18 x 1 / L = 80 |

## Electrical data

|                             |            |
|-----------------------------|------------|
| Operating voltage [V]       | 10...36 DC |
| Current consumption [mA]    | 15; (24 V) |
| Protection class            | II         |
| Reverse polarity protection | yes        |

## Outputs

|                                                      |                    |
|------------------------------------------------------|--------------------|
| Electrical design                                    | PNP                |
| Output function                                      | normally open      |
| Max. voltage drop switching output DC [V]            | 2.5                |
| Permanent current rating of switching output DC [mA] | 250                |
| Switching frequency DC [Hz]                          | 500                |
| Short-circuit protection                             | yes                |
| Type of short-circuit protection                     | yes (non-latching) |
| Overload protection                                  | yes                |

## Monitoring range

|                            |          |
|----------------------------|----------|
| Sensing range [mm]         | 5        |
| Real sensing range Sr [mm] | 5 ± 10 % |
| Operating distance [mm]    | 0...4.05 |

## Accuracy / deviations

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| Correction factor            | steel: 1 / stainless steel: 0.7 / brass: 0.4 / aluminum: 0.3 / copper: 0.2 |
| Hysteresis [% of Sr]         | 1...15                                                                     |
| Switch-point drift [% of Sr] | -10...10                                                                   |

# IG5399



## Inductive sensor

IG-3005-BPKG

### Operating conditions

|                     |      |          |
|---------------------|------|----------|
| Ambient temperature | [°C] | -25...80 |
| Protection          |      | IP 67    |

### Tests / approvals

|      |         |              |
|------|---------|--------------|
| EMC  |         | EN 60947-5-2 |
| MTTF | [years] | 1884         |

### Mechanical data

|                    |      |                  |
|--------------------|------|------------------|
| Weight             | [g]  | 125.7            |
| Housing            |      | Threaded type    |
| Mounting           |      | flush mountable  |
| Dimensions         | [mm] | M18 x 1 / L = 80 |
| Thread designation |      | M18 x 1          |
| Material           |      | PBT              |

### Displays / operating elements

|         |                  |                 |
|---------|------------------|-----------------|
| Display | Switching status | 1 x LED, yellow |
|---------|------------------|-----------------|

### Accessories

|                |              |
|----------------|--------------|
| Items supplied | lock nuts: 2 |
|----------------|--------------|


### Remarks

|               |        |
|---------------|--------|
| Pack quantity | 1 pcs. |
|---------------|--------|

### Electrical connection

Cable: 2 m, PVC; 3 x 0.5 mm<sup>2</sup>

### Connection



BN = Core colors : brown  
BU = blue  
BK = black