

OSR-FPKG



Type of light	Infrared light
Housing	rectangular

Function principle	Retro-reflective sensor
--------------------	-------------------------

Operating voltage	[V]	10...55 DC
Current consumption	[mA]	30; ((24 V))
Protection class		II
Reverse polarity protection		yes
Type of light		Infrared light
Wave length	[nm]	950

Electrical design	PNP
Output function	light-on/dark-on mode; (programmable)
Max. voltage drop switching output DC [V]	2.5
Permanent current rating of switching output DC [mA]	250
Switching frequency DC [Hz]	100
Short-circuit protection	yes
Type of short-circuit protection	yes (non-latching)

OS5016



Retro-reflective sensor

OSR-FPKG

Overload protection	yes
---------------------	-----

Monitoring range

Range referred to prismatic reflector [m]	10; (Prismatic reflector Ø 80 E20005)
Range adjustable	yes

Operating conditions

Ambient temperature [°C]	-25...80
Protection	IP 65

Tests / approvals

EMC	EN 60947-5-2	
MTTF [years]	632	

Mechanical data

Weight [g]	275
Housing	rectangular
Dimensions [mm]	80 x 28 x 95
Material	PPO modified
Lens material	glass
Lens alignment	Side sensing

Displays / operating elements

Display	Switching status	1 x LED, yellow
---------	------------------	-----------------

Accessories

Items supplied	Angle bracket: 1, E20210 screwdrivers
----------------	--

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

terminals: ...1.5 mm²; Cable gland: M20 X 1.5

Connection

