


PA3528



Pressure transmitter with ceramic measuring cell

PA-,25BRBG14-A-ZVG/US/ IV



1 sealing



Product characteristics					
Number of inputs and outputs		Number of analog outputs: 1			
Measuring range		0...0.25 bar	0...250 mbar	0...100.3 inH2O	0...25 kPa
Process connection		threaded connection G 1/4 external thread Internal thread:M5			
Application					
System		gold-plated contacts			
Application		for industrial applications			
Media		liquids and gases			
Medium temperature		[°C] -25...90; (on request: -40...90 °C)			
Min. bursting pressure		30000 mbar	12030 inH2O	3000 kPa	
Pressure rating		6000 mbar	2400 inH2O	600 kPa	
Type of pressure		relative pressure			
Electrical data					
Operating voltage		[V]	9.6...32 DC		
Min. insulation resistance		[MΩ]	100; (500 V DC)		
Protection class		III			
Reverse polarity protection		yes			
Inputs / outputs					
Number of inputs and outputs		Number of analog outputs: 1			
Outputs					
Total number of outputs		1			
Output signal		analog signal			
Number of analog outputs		1			
Analog current output		[mA]	4...20		



Pressure transmitter with ceramic measuring cell

PA-,25BRBG14-A-ZVG/US/ IV

Max. load	[Ω]	720; (Ub = 24 V; (Ub - 9,6 V) / 20 mA)			
Overload protection		yes			
Measuring/setting range					
Measuring range		0...0.25 bar	0...250 mbar	0...100.3 inH2O	0...25 kPa
Accuracy / deviations					
Repeatability	[% of the span]	< 0,1; (with temperature fluctuations < 10 K)			
Characteristics deviation	[% of the span]	< ± 0,25 (BFSL) / < ± 0,5 (LS); (BFSL = Best Fit Straight Line; LS = limit value setting)			
Long-term stability	[% of the span]	< ± 0,05; (per 6 months)			
Temperature coefficient zero point	[% of the span / 10 K]	< ± 0,2; (0...80 °C)			
Temperature coefficient span	[% of the span / 10 K]	< ± 0,3; (0...80 °C)			
Reaction times					
Step response time analog output	[ms]	3			
Operating conditions					
Ambient temperature	[°C]	-25...80			
Storage temperature	[°C]	-40...100			
Protection		IP 65			
Tests / approvals					
EMC	EN 61000-4-2 ESD		4 kV CD / 8 kV AD		
	EN 61000-4-3 HF radiated		30 V/m		
	EN 61000-4-4 Burst		2 kV		
	EN 61000-4-6 HF conducted		10 V		
	radiation of interference		according to the automotive directive 2004/104/EC		
	CISPR 25				
	noise immunity		according to the automotive directive 2004/104/EC		
	ISO 11452-2 HF radiated		100 V/m		
	ISO 7637-2 pulse		severity level 4		
Shock resistance		DIN EN 60068-2-27	50 g (11 ms)		
		DIN EN 61373	Category 3		
Vibration resistance		DIN EN 60068-2-6	20 g (10...2000 Hz)		
		DIN EN 61373	Category 2		
MTTF	[years]	514			
Pressure equipment directive		sound engineering practice; can be used for group 2 fluids; group 1 fluids on request			
Railway applications		DIN EN 50155 / IEC 60571		Klasse T3, C1, S1	
Mechanical data					
Weight	[g]	217			
Housing		tubular			
Dimensions	[mm]	Ø 30 / L = 79.5			
Material		stainless steel (1.4404 / 316L); FKM; PA; EPDM/X			
Materials (wetted parts)		stainless steel (1.4305 / 303); ceramics; sealing: FKM DIN 3869-14			

PA3528



Pressure transmitter with ceramic measuring cell

PA-,25BRBG14-A-ZVG/US/ IV


Min. pressure cycles	100 million
Process connection	threaded connection G 1/4 external thread Internal thread:M5
Restrictor element integrated	no (can be retrofitted)

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection

Connector: 1 x M12; coding: A; Contacts: gold-plated



Connection

