


Inductive analog sensor


NBB5-18GM60-I3



- Inductive analog
- Output 0 mA ... 20 mA
- Flush mounting



Dimensions



Technical Data

General specifications

Output type	Analog current output
Installation	flush
Output polarity	DC
Measurement range	1 ... 5 mm
Output type	3-wire

Nominal ratings

Operating voltage	U_B	10 ... 30 V DC typ. 20 V DC
Reverse polarity protection		yes
Repeat accuracy		0 ... 80 μ m
No-load supply current	I_0	≤ 12 mA

Analog output

Output type		0 ... 20 mA
Slope of output characteristic		5 mA / mm
Linearity error		≤ ± 5 % of full-scale value
Load resistor		≤ 1000 Ω typ. 500 Ω
Rate of current rise		
0 ... 20 mA		max. 38.9 A/s
20 ... 0 mA		max. 13.9 A/s
Recovery time		1 ... 10 ms , typ. 5 ms

Release date: 2024-05-28 Date of issue: 2024-06-08 Filename: 303096_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data


Adjustment tolerance zero point	≤ ± 5 % of full-scale value
Temperature drift	≤ ± 0.15 %/K of full-scale value
Residual ripple	± 125 µA
Compliance with standards and directives	
Standard conformity	
Standards	EN IEC 60947-5-2
Approvals and certificates	
UL approval	cULus Listed, Class 2 Power Source
CCC approval	CCC approval / marking not required for products rated ≤36 V
Ambient conditions	
Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications	
Connection type	cable PVC , 2 m
Core cross section	0.5 mm²
Housing material	brass, nickel-plated
Sensing face	PBT
Degree of protection	IP67
Cable	
Cable diameter	4.6 mm ± 0.2 mm
Bending radius	> 10 x cable diameter
Dimensions	
Length	60 mm
Diameter	18 mm

Connection



Characteristic Curve


Output characteristics



Release date: 2024-05-28 Date of issue: 2024-06-08 Filename: 303096_eng.pdf

Characteristic Curve

Reduction factor



Release date: 2024-05-28 Date of issue: 2024-06-08 Filename: 303096_eng.pdf