

- 8 mm flush
- 3-wire DC
- Amp connector



Technical drawing of the LED module showing top and side views with dimensions.

Top View Dimensions:

- Overall width: 73.6
- Distance from left edge to first LED: 56.5
- Distance between LEDs: 37.8
- Distance from left edge to second LED: 31
- Distance from left edge to third LED: 10
- Distance from second LED to right edge: 14.5
- Overall height: 25
- Distance from top edge to LED row: 15
- Distance from LED row to right edge: 16.2

Side View Dimensions:

- Overall height: 16
- Distance from top edge to LED row: 10.1
- Distance from LED row to bottom edge: 8.5
- LED label pointing to the LED row.
- LED row diameter: $\varnothing 4.3$
- Bottom edge diameter: $\varnothing 7.3$
- Distance from LED row to right edge: 12.5

General specifications

Switching function		Normally closed (NC)
Output type		PNP
Rated operating distance	s _n	8 mm
Installation		flush
Output polarity		DC
Assured operating distance	s _a	0 ... 6.5 mm
Reduction factor r _{Al}		0.3
Reduction factor r _{Cu}		0.2
Reduction factor r ₃₀₄		0.6
Reduction factor r _{Brass}		0.35
Output type		3-wire
Nominal ratings		
Operating voltage	U _B	10 ... 60 V DC
Switching frequency	f	0 ... 250 Hz
Hysteresis	H	typ. 5 %
Reverse polarity protection		reverse polarity protected

Release date: 2024-01-02 Date of issue: 2024-01-02 Filename: 266706_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com




Technical Data

Short-circuit protection		pulsing
Voltage drop	U_d	$\leq 2.5\text{ V}$
Operating current	I_L	0 ... 200 mA
Off-state current	I_r	0 ... 0.1 mA
No-load supply current	I_0	$\leq 10\text{ mA}$
Time delay before availability	t_v	$\leq 50\text{ ms}$
Switching state indicator		LED yellow
Functional safety related parameters		
MTTF _d		1937 a
Mission Time (T _M)		20 a
Diagnostic Coverage (DC)		0 %
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Ambient conditions		
Ambient temperature		-35 ... 70 °C (-31 ... 158 °F)
Storage temperature		-40 ... 85 °C (-40 ... 185 °F)
Mechanical specifications		
Connection type		Connector plug , AMP connector
Housing material		PBT , black
Degree of protection		IP67
Dimensions		
Height		10 mm
Width		25 mm
Length		73 mm
Note		Tightening torque: 5 Nm

Connection



Connection Assignment



Release date: 2024-01-02 Date of issue: 2024-01-02 Filename: 266706_eng.pdf