

- 10 mm non-flush
- 3-wire DC



Technical drawing of the LED module showing front and side views with dimensions.

Front View (Left):

- Overall width: 25
- Overall height: 38.5
- Distance from top edge to the center of the LED: 18
- Distance from left edge to the center of the LED: 12.5 (indicated by a dashed line)
- LED diameter: 18
- Distance from the bottom of the LED to the bottom edge of the module: 4.3
- Distance from the center of the LED to the right edge of the module: 12.5 (indicated by a dashed line)
- Distance from the center of the LED to the right edge of the module: 12.5 (indicated by a dashed line)
- Distance from the center of the LED to the right edge of the module: 12.5 (indicated by a dashed line)
- Distance from the center of the LED to the right edge of the module: 12.5 (indicated by a dashed line)

Side View (Right):

- Overall width: 25.5
- Overall height: 10
- Distance from top edge to the center of the LED: 7
- LED diameter: M12 x 1

General specifications

Switching function		Normally open (NO)
Output type		PNP
Rated operating distance	s _n	10 mm
Installation		non-flush
Output polarity		DC
Assured operating distance	s _a	0 ... 8.1 mm

Release date: 2024-05-27 Date of issue: 2024-05-28 Filename: 082692_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com




Technical Data

Reduction factor r_{Al}		0.3
Reduction factor r_{Cu}		0.2
Reduction factor r_{304}		0.6
Output type		3-wire
Nominal ratings		
Operating voltage	U_B	10 ... 30 V DC
Switching frequency	f	0 ... 500 Hz
Hysteresis	H	typ. 5%
Reverse polarity protection		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 100 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.1 μ A at 25 °C
No-load supply current	I_0	≤ 15 mA
Switching state indicator		LED, yellow
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤ 36 V
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		Connector plug M12 x 1 , 4-pin
Housing material		PBT
Sensing face		PBT
Degree of protection		IP67
Dimensions		
Height		25.5 mm
Width		25 mm
Length		38.5 mm

Connection



Connection Assignment



Release date: 2024-05-27 Date of issue: 2024-05-28 Filename: 082692_eng.pdf

Connection Assignment

Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Release date: 2024-05-27 Date of issue: 2024-05-28 Filename: 082692_eng.pdf