



# Inductive sensor NBN12-18GM50-E3-V3



- 12 mm non-flush
- Increased operating distance
- Extended temperature range  
-40 ... +85 °C
- Extended operating voltage range
- Flexible use with versatile mounting opportunities



## Dimensions



## Technical Data

### General specifications

|                            |       |                                                                             |
|----------------------------|-------|-----------------------------------------------------------------------------|
| Switching function         |       | Normally closed (NC)                                                        |
| Output type                |       | PNP                                                                         |
| Rated operating distance   | $s_n$ | 12 mm                                                                       |
| Installation               |       | non-flush                                                                   |
| Output polarity            |       | DC                                                                          |
| Assured operating distance | $s_a$ | 0 ... 9.72 mm                                                               |
| Actuating element          |       | mild steel, e. g. 1.0037, SR235JR (formerly St37-2)<br>36 mm x 36 mm x 1 mm |
| Reduction factor $r_{AI}$  |       | 0.49                                                                        |

Release date: 2024-05-27 Date of issue: 2024-05-30 Filename: 326161-0230\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Technical Data

|                                                 |           |                                                                    |
|-------------------------------------------------|-----------|--------------------------------------------------------------------|
| Reduction factor $r_{Cu}$                       |           | 0.46                                                               |
| Reduction factor $r_{304}$                      |           | 0.75                                                               |
| Reduction factor $r_{Brass}$                    |           | 0.55                                                               |
| Output type                                     |           | 3-wire                                                             |
| <b>Nominal ratings</b>                          |           |                                                                    |
| Operating voltage                               | $U_B$     | 5 ... 36 V                                                         |
| Switching frequency                             | $f$       | 0 ... 1300 Hz                                                      |
| Hysteresis                                      | $H$       | typ. 5 %                                                           |
| Reverse polarity protection                     |           | reverse polarity protected                                         |
| Short-circuit protection                        |           | pulsing                                                            |
| Voltage drop                                    | $U_d$     | $\leq 1$ V                                                         |
| Operating current                               | $I_L$     | 0 ... 200 mA                                                       |
| Off-state current                               | $I_r$     | max. 20 $\mu$ A                                                    |
| No-load supply current                          | $I_0$     | $\leq 10$ mA                                                       |
| Time delay before availability                  | $t_v$     | $\leq 10$ ms                                                       |
| Switching state indicator                       |           | Multihole-LED, yellow                                              |
| <b>Functional safety related parameters</b>     |           |                                                                    |
| MTTF <sub>d</sub>                               |           | 1707 a                                                             |
| Mission Time ( $T_M$ )                          |           | 20 a                                                               |
| Diagnostic Coverage (DC)                        |           | 0 %                                                                |
| <b>Compliance with standards and directives</b> |           |                                                                    |
| Standard conformity                             |           |                                                                    |
| Standards                                       |           | EN IEC 60947-5-2                                                   |
| <b>Approvals and certificates</b>               |           |                                                                    |
| Protection class                                |           | II                                                                 |
| Rated insulation voltage                        | $U_i$     | 36 V                                                               |
| Rated impulse withstand voltage                 | $U_{imp}$ | 500 V                                                              |
| UL approval                                     |           | cULus Listed, General Purpose, Class 2 Power Source                |
| CCC approval                                    |           | CCC approval / marking not required for products rated $\leq 36$ V |
| <b>Ambient conditions</b>                       |           |                                                                    |
| Ambient temperature                             |           | -40 ... 85 °C (-40 ... 185 °F)                                     |
| Storage temperature                             |           | -40 ... 85 °C (-40 ... 185 °F)                                     |
| <b>Mechanical specifications</b>                |           |                                                                    |
| Connection type                                 |           | Connector plug                                                     |
| Housing material                                |           | brass , white bronze coated                                        |
| Sensing face                                    |           | PBT , green                                                        |
| Degree of protection                            |           | IP67                                                               |
| Connector                                       |           |                                                                    |
| Threading                                       |           | M8 x 1                                                             |
| Number of pins                                  |           | 3                                                                  |
| Mass                                            |           | 58 g                                                               |
| Dimensions                                      |           |                                                                    |
| Length                                          |           | 40 mm                                                              |
| Diameter                                        |           | 18 mm                                                              |
| Mounting                                        |           | with nuts, M18                                                     |
| Tightening torque                               |           | 0 ... 30 Nm                                                        |
| <b>General information</b>                      |           |                                                                    |
| Scope of delivery                               |           | 2 self locking nuts in scope of delivery                           |

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |