




Inductive sensor NBN8-18GK50-A2

- 8 mm non-flush
- Antivalent outputs
- Plastic housing



Dimensions



Technical Data

General specifications			
Switching function			complementary
Output type			PNP
Rated operating distance	s_n		8 mm
Installation			non-flush
Output polarity			DC
Assured operating distance	s_a		0 ... 6.48 mm
Reduction factor r_{AI}			0.45
Reduction factor r_{Cu}			0.4
Reduction factor r_{304}			0.7
Output type			4-wire
Nominal ratings			
Operating voltage	U_B		10 ... 30 V
Switching frequency	f		0 ... 500 Hz
Reverse polarity protection			reverse polarity protected
Short-circuit protection			pulsing
Voltage drop	U_d		≤ 3 V

Release date: 2024-05-28 Date of issue: 2024-06-06 Filename: 806948_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Operating current	I _L	0 ... 200 mA
No-load supply current	I ₀	≤ 25 mA
Switching state indicator		LED, yellow
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		cablE PVC , 2 m
Core cross section		4 x 0.34 mm²
Housing material		PBT
Sensing face		PBT
Degree of protection		IP69K
Dimensions		
Length		50 mm
Diameter		18 mm

Connection

