

# Inductive sensor


## NBN8-18GM80-WO-V93



- 8 mm non-flush
- 2-wire AC



### Dimensions



### Technical Data

#### General specifications

|                            |       |                          |
|----------------------------|-------|--------------------------|
| Switching function         |       | Normally closed (NC)     |
| Output type                |       | Two-wire                 |
| Rated operating distance   | $s_n$ | 8 mm                     |
| Installation               |       | non-flush                |
| Output polarity            |       | AC                       |
| Assured operating distance | $s_a$ | 0 ... 6.48 mm            |
| Actual operating distance  | $s_r$ | 7.2 ... 8.8 mm typ. 8 mm |
| Reduction factor $r_{AI}$  |       | 0.4                      |
| Reduction factor $r_{Cu}$  |       | 0.4                      |
| Reduction factor $r_{304}$ |       | 0.7                      |
| Output type                |       | 2-wire                   |

#### Nominal ratings

|                             |       |                                                |
|-----------------------------|-------|------------------------------------------------|
| Operating voltage           | $U_B$ | 20 ... 253 V                                   |
| Switching frequency         | $f$   | 0 ... 20 Hz                                    |
| Hysteresis                  | $H$   | typ. 7.5 %                                     |
| Reverse polarity protection |       | reverse polarity tolerant                      |
| Voltage drop                | $U_d$ | < 5 V ( $I_L > 50$ mA); < 8 V ( $I_L < 50$ mA) |

Release date: 2024-05-28 Date of issue: 2024-06-05 Filename: 124320\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**


Technical Data

|                                          |                |                                                                                                                                                                                                                                                                |
|------------------------------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Momentary current<br>(20 ms, 0.1 Hz)     |                | 0 ... 1600 mA                                                                                                                                                                                                                                                  |
| Operating current                        | I <sub>L</sub> | 5 ... 200 mA                                                                                                                                                                                                                                                   |
| Off-state current                        | I <sub>r</sub> | 0 ... 1.7 mA typ.                                                                                                                                                                                                                                              |
| Time delay before availability           | t <sub>v</sub> | ≤ 30 ms                                                                                                                                                                                                                                                        |
| Operating voltage indicator              |                | LED, green                                                                                                                                                                                                                                                     |
| Switching state indicator                |                | LED, yellow                                                                                                                                                                                                                                                    |
| Compliance with standards and directives |                |                                                                                                                                                                                                                                                                |
| Standard conformity                      |                |                                                                                                                                                                                                                                                                |
| Standards                                |                | EN IEC 60947-5-2                                                                                                                                                                                                                                               |
| Approvals and certificates               |                |                                                                                                                                                                                                                                                                |
| UL approval                              |                | cULus Listed, General Purpose                                                                                                                                                                                                                                  |
| CSA approval                             |                | cCSAus Listed, General Purpose                                                                                                                                                                                                                                 |
| CCC approval                             |                | Certified by China Compulsory Certification (CCC)                                                                                                                                                                                                              |
| Ambient conditions                       |                |                                                                                                                                                                                                                                                                |
| Ambient temperature                      |                | -25 ... 70 °C (-13 ... 158 °F)                                                                                                                                                                                                                                 |
| Mechanical specifications                |                |                                                                                                                                                                                                                                                                |
| Connection type                          |                | Connector plug 7/8 inch-16 UN , 3-pin                                                                                                                                                                                                                          |
| Housing material                         |                | brass, nickel-plated                                                                                                                                                                                                                                           |
| Sensing face                             |                | PBT                                                                                                                                                                                                                                                            |
| Degree of protection                     |                | IP67                                                                                                                                                                                                                                                           |
| Dimensions                               |                |                                                                                                                                                                                                                                                                |
| Length                                   |                | 80 mm                                                                                                                                                                                                                                                          |
| Diameter                                 |                | 18 mm                                                                                                                                                                                                                                                          |
| Note                                     |                | 1) In the temperature range below 0 °C, permissible operating voltage U <sub>b</sub> 80...253 V<br>Safety fuse ≤ 0.8 A (quick-blow) according to IEC 60127-2 Sheet 1<br>Recommendation: after a short circuit, check that the device is functioning correctly. |

Connection



Connection Assignment



|             |  |    |         |
|-------------|--|----|---------|
| Wire colors |  |    |         |
| 1           |  | GN | (green) |
| 2           |  | BK | (black) |
| 3           |  | WH | (white) |