


NCB1,5-8GM25-N0-Y295009



- 1.5 mm flush



Dimensions



Technical Data

General specifications

Output type		NAMUR
Rated operating distance	S_n	1.5 mm
Installation		flush
Assured operating distance	S_a	0 ... 1.215 mm
Actual operating distance	S_r	1.35 ... 1.65 mm typ.
Reduction factor r_{Al}		0.3
Reduction factor r_{Cu}		0.2
Reduction factor r_{304}		0.7
Output type		2-wire

Nominal ratings

Nominal voltage	U _o	8.2 V (R _i approx. 1 kΩ)
Switching frequency	f	0 ... 2000 Hz
Hysteresis	H	1 ... 10 % typ. 3 %
Reverse polarity protection		reverse polarity protected
Short-circuit protection		yes
Suitable for 2:1 technology		yes , Reverse polarity protection diode not required
Current consumption		
Measuring plate not detected		min. 3 mA
Measuring plate detected		≤ 1 mA

Functional safety related parameters

MTTF _d	3590 a
Mission Time (T _M)	20 a

Release date: 2024-12-11 Date of issue: 2024-12-11 Filename: 70133333_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sq.pepperl-fuchs.com



Technical Data

Diagnostic Coverage (DC)		0 %
Compliance with standards and directives		
Standard conformity		
NAMUR		EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards		EN IEC 60947-5-2
Approvals and certificates		
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 100 °C (-13 ... 212 °F)
Storage temperature		-40 ... 100 °C (-40 ... 212 °F)
Mechanical specifications		
Connection type		cable
Connection assembly		Protective hose : stainless steel AISI 304L screwed connection : MS58 nickel-plated
Housing material		Stainless steel 1.4305 / AISI 303
Sensing face		LCP
Degree of protection		IP67
Cable		
Wire end ferrules		yes
Cable diameter		2.6 mm ± 0.2 mm
Bending radius		> 10 x cable diameter
Material		PVC
Color		blue
Number of cores		2
Core cross section		0.14 mm²
Length	L	2 m
Cable protection		Protective hose 40 cm
Dimensions		
Length		25 mm
Diameter		8 mm
General information		
Use in the hazardous area		see instruction manuals

Connection



Release date: 2024-12-11 Date of issue: 2024-12-11 Filename: 70133333_eng.pdf