



# Inductive sensor NEB3-8GM40-E3-PUR



- 3 mm flush
- Increased operating distance
- Extended temperature range  
-40 ... +85 °C



## Dimensions



## Technical Data

### General specifications

|                              |                                                                           |               |
|------------------------------|---------------------------------------------------------------------------|---------------|
| Switching function           | Normally closed (NC)                                                      |               |
| Output type                  |                                                                           | PNP           |
| Rated operating distance     | $s_n$                                                                     | 3 mm          |
| Installation                 |                                                                           | flush         |
| Output polarity              |                                                                           | DC            |
| Assured operating distance   | $s_a$                                                                     | 0 ... 2.43 mm |
| Actuating element            | mild steel, e. g. 1.0037, SR235JR (formerly St37-2)<br>9 mm x 9 mm x 1 mm |               |
| Reduction factor $r_{Al}$    |                                                                           | 0.5           |
| Reduction factor $r_{Cu}$    |                                                                           | 0.4           |
| Reduction factor $r_{304}$   |                                                                           | 0.75          |
| Reduction factor $r_{Brass}$ |                                                                           | 0.5           |
| Output type                  |                                                                           | 3-wire        |

### Nominal ratings

|                             |       |                            |
|-----------------------------|-------|----------------------------|
| Operating voltage           | $U_B$ | 5 ... 30 V                 |
| Switching frequency         | $f$   | 0 ... 3500 Hz              |
| Hysteresis                  | $H$   | typ. 5%                    |
| Reverse polarity protection |       | reverse polarity protected |
| Short-circuit protection    |       | pulsing                    |
| Voltage drop                | $U_d$ | $\leq 1.5$ V               |
| Operating current           | $I_L$ | 0 ... 100 mA               |
| Off-state current           | $I_r$ | 0 ... 0.2 mA               |
| No-load supply current      | $I_0$ | $\leq 10$ mA               |

Release date: 2024-05-28 Date of issue: 2024-06-01 Filename: 304615-0165\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

### Technical Data

|                                                 |       |                                                                            |
|-------------------------------------------------|-------|----------------------------------------------------------------------------|
| Time delay before availability                  | $t_v$ | $\leq 100 \text{ ms}$                                                      |
| Switching state indicator                       |       | LED, yellow                                                                |
| <b>Functional safety related parameters</b>     |       |                                                                            |
| MTTF <sub>d</sub>                               |       | 960 a                                                                      |
| Mission Time (T <sub>M</sub> )                  |       | 20 a                                                                       |
| Diagnostic Coverage (DC)                        |       | 0 %                                                                        |
| <b>Compliance with standards and directives</b> |       |                                                                            |
| Standard conformity                             |       |                                                                            |
| Standards                                       |       | EN IEC 60947-5-2                                                           |
| <b>Approvals and certificates</b>               |       |                                                                            |
| UL approval                                     |       | cULus Listed, General Purpose, Class 2 Power Source                        |
| CCC approval                                    |       | CCC approval / marking not required for products rated $\leq 36 \text{ V}$ |
| <b>Ambient conditions</b>                       |       |                                                                            |
| Ambient temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                                             |
| Storage temperature                             |       | -40 ... 85 °C (-40 ... 185 °F)                                             |
| <b>Mechanical specifications</b>                |       |                                                                            |
| Connection type                                 |       | cable PUR , 2 m                                                            |
| Core cross section                              |       | 0.14 mm <sup>2</sup>                                                       |
| Housing material                                |       | brass, nickel-plated                                                       |
| Sensing face                                    |       | LCP                                                                        |
| Degree of protection                            |       | IP65 / IP66 / IP67                                                         |
| Cable                                           |       |                                                                            |
| Cable diameter                                  |       | 3.3 mm $\pm$ 0.15 mm                                                       |
| Bending radius                                  |       | > 10 x cable diameter                                                      |
| Dimensions                                      |       |                                                                            |
| Length                                          |       | 40 mm                                                                      |
| Diameter                                        |       | 8 mm                                                                       |
| <b>General information</b>                      |       |                                                                            |
| Scope of delivery                               |       | 2 hex nuts included                                                        |

### Connection Assignment



Release date: 2024-05-28 Date of issue: 2024-06-01 Filename: 304615-0165\_eng.pdf