

Inductive sensor


NJ0,2-10GM-N-Y199308



- 0.2 mm flush
- Sensor with dead stop



Dimensions



Technical Data

General specifications

Switching function		Normally closed (NC)
Output type		NAMUR
Rated operating distance	s_n	0.2 mm
Installation		flush
Assured operating distance	s_a	0 ... 0.2 mm
Reduction factor r_{AI}		0.4
Reduction factor r_{Cu}		0.3
Reduction factor r_{304}		0.85
Output type		2-wire

Nominal ratings

Nominal voltage	U_o	8 V
Operating voltage	U_B	5 ... 25 V
Switching frequency	f	0 ... 100 Hz
Hysteresis	H	typ. %
Current consumption		
Measuring plate not detected		≥ 3 mA at nominal voltage

Release date: 2024-05-27 Date of issue: 2024-05-27 Filename: 199308_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Measuring plate detected		≤ 1 mA at nominal voltage
Compliance with standards and directives		
Standard conformity		
NAMUR		EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Axial load, max.	F	0 ... 1200 N
Connection type		5 m PVC cable (suitable for drag chain)
Core cross section		0.34 mm²
Housing material		stainless steel 1.4034 / AISI 420
Degree of protection		IP67
Dimensions		
Length		27 mm
Diameter		10 mm

Connection



Release date: 2024-05-27 Date of issue: 2024-05-27 Filename: 199308_eng.pdf