





Inductive sensor NJ10-30GK50-A2-10M

■ 10 mm flush



Dimensions



Technical Data

General specifications		
Switching function		complementary
Output type		PNP
Rated operating distance	s_n	10 mm
Installation		flush
Output polarity		DC
Assured operating distance	s_a	0 ... 8.1 mm
Actual operating distance	s_r	9 ... 11 mm typ. 10 mm
Reduction factor r_{Al}		0.4
Reduction factor r_{Cu}		0.38
Reduction factor r_{304}		0.71
Reduction factor r_{Brass}		0.45
Output type		4-wire
Nominal ratings		
Operating voltage	U_B	10 ... 60 V
Switching frequency	f	0 ... 500 Hz
Hysteresis	H	typ. 5 %

Release date: 2024-05-27 Date of issue: 2024-05-29 Filename: 70135029_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Reverse polarity protection		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	$\leq 2.8 \text{ V}$
Voltage drop at I_L		
Voltage drop $I_L = 10 \text{ mA}$, switching element on	U_d	$0.9 \dots 2.4 \text{ V typ. } 1.7 \text{ V}$
Voltage drop $I_L = 20 \text{ mA}$, switching element on	U_d	$0.9 \dots 2.4 \text{ V typ. } 1.7 \text{ V}$
Voltage drop $I_L = 50 \text{ mA}$, switching element on	U_d	$0.9 \dots 2.5 \text{ V typ. } 1.7 \text{ V}$
Voltage drop $I_L = 100 \text{ mA}$, switching element on	U_d	$1 \dots 2.6 \text{ V typ. } 1.8 \text{ V}$
Voltage drop $I_L = 200 \text{ mA}$, switching element on	U_d	$1.2 \dots 2.8 \text{ V typ. } 2 \text{ V}$
Operating current	I_L	$0 \dots 400 \text{ mA}$
Off-state current	I_r	$0 \dots 0.5 \text{ mA typ. } 0.01 \text{ mA}$
No-load supply current	I_0	$\leq 9 \text{ mA}$
Switching state indicator		LED, yellow
Functional safety related parameters		
MTTF _d		1130 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose, Class 2 Power Source
Ambient conditions		
Ambient temperature		$-25 \dots 70 \text{ }^\circ\text{C} (-13 \dots 158 \text{ }^\circ\text{F})$
Storage temperature		$-25 \dots 85 \text{ }^\circ\text{C} (-13 \dots 185 \text{ }^\circ\text{F})$
Mechanical specifications		
Connection type		cable
Housing material		PBT
Sensing face		PBT
Degree of protection		IP68
Cable		
Wire end ferrules		yes
Cable diameter		$6.8 \text{ mm} \pm 0.2 \text{ mm}$
Bending radius		$> 10 \times \text{cable diameter}$
Material		PVC
Color		grey
Number of cores		4
Core cross section		0.75 mm^2
Length	L	10 m
Dimensions		
Length		50 mm
Diameter		30 mm

Connection



Release date: 2024-05-27 Date of issue: 2024-05-29 Filename: 70135029_eng.pdf