





Inductive sensor NJ25-50-N-15M

- 25 mm non-flush
- NAMUR output
- 15 m connection cable



Dimensions



Technical Data

General specifications

Switching function	Normally closed (NC)	
Output type	NAMUR	
Rated operating distance	s_n	25 mm
Installation	non-flush	
Assured operating distance	s_a	0 ... 20.25 mm
Reduction factor r_{AI}	0.4	
Reduction factor r_{Cu}	0.3	
Reduction factor r_{304}	0.85	
Output type	2-wire	

Nominal ratings

Nominal voltage	U_o	8.2 V (R_i approx. 1 k Ω)
Switching frequency	f	0 ... 250 Hz
Current consumption		
Measuring plate not detected		min. 3 mA
Measuring plate detected		≤ 1 mA

Release date: 2024-10-09 Date of issue: 2024-10-09 Filename: 70133328_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Compliance with standards and directives

Standard conformity

NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999
-------	---

Standards	EN IEC 60947-5-2
-----------	------------------

Approvals and certificates

IECEx approval

Equipment protection level Gb	IECEx PTB 11.0037X
Equipment protection level Da	IECEx PTB 11.0037X
Equipment protection level Mb	IECEx PTB 11.0037X

ATEX approval

Equipment protection level Gb	PTB 00 ATEX 2048 X
Equipment protection level Da	PTB 00 ATEX 2048 X

UL approval

	cULus Listed, General Purpose
--	-------------------------------

CCC approval

Hazardous Location	2020322315002258
--------------------	------------------

CML approval

	on request
--	------------

ANZEx

	18.3018X
--	----------

Ambient conditions

Ambient temperature	-25 ... 100 °C (-13 ... 212 °F)
---------------------	---------------------------------

Mechanical specifications

Connection type		cable
Housing material		PBT
Sensing face		PBT
Degree of protection		IP67
Cable		
Wire end ferrules		yes
Cable diameter		6 mm ± 0.2 mm
Bending radius		> 10 x cable diameter
Material		PVC
Color		blue
Number of cores		2
Core cross section		0.75 mm ²
Length	L	15 m
Mass		935 g
Tightening torque, fastening screws		≤ 1.8 Nm
Dimensions		
Length		40 mm
Diameter		50 mm

General information

Use in the hazardous area	see instruction manuals
---------------------------	-------------------------

Connection

