

# Inductive sensor


## NJ3-18GK-S1N-5M



- Nonferrous targets
- 3 mm flush in ST37 / 1.0037
- Usable up to SIL 3 acc. to IEC 61508
- Degree of protection IP68
- ATEX & IECEx certifications
- ATEX/IECEx Zone 2/22



### Dimensions



### Technical Data

#### General specifications

|                              |                                                                                                                                                                                                                                                                                                                                                                                             |                     |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| Switching function           | Normally open (NO)                                                                                                                                                                                                                                                                                                                                                                          |                     |
| Output type                  | NAMUR with safety function                                                                                                                                                                                                                                                                                                                                                                  |                     |
| Rated operating distance     | $s_n$                                                                                                                                                                                                                                                                                                                                                                                       | 3 mm                |
| Installation                 | flush in mild steel                                                                                                                                                                                                                                                                                                                                                                         |                     |
| Assured operating distance   | $s_a$                                                                                                                                                                                                                                                                                                                                                                                       | 0 ... 2.4 mm        |
| Actual operating distance    | $s_r$                                                                                                                                                                                                                                                                                                                                                                                       | 2.7 ... 3.3 mm typ. |
| Reduction factor $r_{Al}$    | 1                                                                                                                                                                                                                                                                                                                                                                                           |                     |
| Reduction factor $r_{Cu}$    | 1                                                                                                                                                                                                                                                                                                                                                                                           |                     |
| Reduction factor $r_{304}$   | 0                                                                                                                                                                                                                                                                                                                                                                                           |                     |
| Safety Integrity Level (SIL) | up to SIL3 acc. to IEC 61508 <b>Danger!</b> In safety-related applications the sensor must be operated with a qualified fail safe interface from Pepperl+Fuchs, such as KFD2-SH-EX1. Consider the "exida Functional Safety Assessment" document which is available on <a href="http://www.pepperl-fuchs.com">www.pepperl-fuchs.com</a> as an integral part of this product's documentation. |                     |
| Output type                  | 2-wire                                                                                                                                                                                                                                                                                                                                                                                      |                     |

#### Nominal ratings

|                              |       |                                      |
|------------------------------|-------|--------------------------------------|
| Nominal voltage              | $U_o$ | 8.2 V ( $R_i$ approx. 1 k $\Omega$ ) |
| Switching frequency          | $f$   | 0 ... 200 Hz                         |
| Current consumption          |       |                                      |
| Measuring plate not detected |       | $\leq 1$ mA                          |
| Measuring plate detected     |       | $\geq 3$ mA                          |

#### Functional safety related parameters

|                              |       |
|------------------------------|-------|
| Safety Integrity Level (SIL) | SIL 3 |
|------------------------------|-------|

Release date: 2024-05-28 Date of issue: 2024-06-02 Filename: 70133168\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
[www.pepperl-fuchs.com](http://www.pepperl-fuchs.com)

USA: +1 330 486 0001  
[fa-info@us.pepperl-fuchs.com](mailto:fa-info@us.pepperl-fuchs.com)

Germany: +49 621 776 1111  
[fa-info@de.pepperl-fuchs.com](mailto:fa-info@de.pepperl-fuchs.com)


Singapore: +65 6779 9091  
[fa-info@sg.pepperl-fuchs.com](mailto:fa-info@sg.pepperl-fuchs.com)

PEPPERL+FUCHS

## Technical Data

|                                                 |   |                                 |
|-------------------------------------------------|---|---------------------------------|
| MTTF <sub>d</sub>                               |   | 10660 a                         |
| Mission Time (T <sub>M</sub> )                  |   | 20 a                            |
| Diagnostic Coverage (DC)                        |   | 0 %                             |
| <b>Compliance with standards and directives</b> |   |                                 |
| Standard conformity                             |   |                                 |
| Standards                                       |   | EN IEC 60947-5-2                |
| <b>Approvals and certificates</b>               |   |                                 |
| IECEX approval                                  |   |                                 |
| Equipment protection level Ga                   |   | IECEX PTB 11.0092X              |
| Equipment protection level Gb                   |   | IECEX PTB 11.0092X              |
| Equipment protection level Gc (ec)              |   | IECEX TUR 21.0017X              |
| Equipment protection level Da                   |   | IECEX PTB 11.0092X              |
| Equipment protection level Dc (tc)              |   | IECEX TUR 21.0018X              |
| Equipment protection level Mb                   |   | IECEX PTB 11.0092X              |
| ATEX approval                                   |   |                                 |
| Equipment protection level Ga                   |   | PTB 00 ATEX 2049 X              |
| Equipment protection level Gb                   |   | PTB 00 ATEX 2049 X              |
| Equipment protection level Gc (ec)              |   | TÜV 20 ATEX 8523 X              |
| Equipment protection level Da                   |   | PTB 00 ATEX 2049 X              |
| Equipment protection level Dc (tc)              |   | TÜV 20 ATEX 8524 X              |
| UL approval                                     |   |                                 |
| Ordinary Location                               |   | E87056                          |
| Hazardous Location                              |   | E501628                         |
| Control drawing                                 |   | 116-0454                        |
| CCC approval                                    |   |                                 |
| Hazardous Location                              |   | 2020322315002308                |
| NEPSI approval                                  |   |                                 |
| NEPSI certificate                               |   | GYJ16.1392X                     |
| <b>Ambient conditions</b>                       |   |                                 |
| Ambient temperature                             |   | -25 ... 100 °C (-13 ... 212 °F) |
| <b>Mechanical specifications</b>                |   |                                 |
| Connection type                                 |   | cable                           |
| Housing material                                |   | Crastin (PBT), black            |
| Sensing face                                    |   | Crastin (PBT), black            |
| Degree of protection                            |   | IP68                            |
| Cable                                           |   |                                 |
| Cable diameter                                  |   | 6.8 mm ± 0.2 mm                 |
| Bending radius                                  |   | > 10 x cable diameter           |
| Material                                        |   | silicone                        |
| Core cross section                              |   | 0.75 mm <sup>2</sup>            |
| Length                                          | L | 5 m                             |
| Dimensions                                      |   |                                 |
| Length                                          |   | 39 mm                           |
| Diameter                                        |   | 18 mm                           |
| Note                                            |   | only for non-ferrous metal      |
| <b>General information</b>                      |   |                                 |
| Use in the hazardous area                       |   | see instruction manuals         |

Connection



Release date: 2024-05-28 Date of issue: 2024-06-02 Filename: 70133168\_eng.pdf

## Application

**Danger!**

In safety-related applications the sensor must be operated with a qualified fail safe interface from Pepperl+Fuchs, such as KFD2-SH-EX1.

Consider the "exida Functional Safety Assessment" document which is available on [www.pepperl-fuchs.com](http://www.pepperl-fuchs.com) as an integral part of this product's documentation.