


# Inductive sensor NJ5-18GM50-E2-V1



- Comfort series
- 5 mm flush



## Dimensions



## Technical Data

| General specifications       |       |                          |
|------------------------------|-------|--------------------------|
| Switching function           |       | Normally open (NO)       |
| Output type                  |       | PNP                      |
| Rated operating distance     | $s_n$ | 5 mm                     |
| Installation                 |       | flush                    |
| Output polarity              |       | DC                       |
| Assured operating distance   | $s_a$ | 0 ... 4.05 mm            |
| Actual operating distance    | $s_r$ | 4.5 ... 5.5 mm typ. 5 mm |
| Reduction factor $r_{Al}$    |       | 0.2                      |
| Reduction factor $r_{Cu}$    |       | 0.15                     |
| Reduction factor $r_{304}$   |       | 0.62                     |
| Reduction factor $r_{Brass}$ |       | 0.32                     |
| Output type                  |       | 3-wire                   |
| Nominal ratings              |       |                          |
| Operating voltage            | $U_B$ | 10 ... 60 V              |
| Switching frequency          | $f$   | 0 ... 1500 Hz            |
| Hysteresis                   | $H$   | 1 ... 10 % typ. 6 %      |

Release date: 2024-12-10 Date of issue: 2024-12-11 Filename: 282958\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**


## Technical Data

|                                                                     |       |                                                              |
|---------------------------------------------------------------------|-------|--------------------------------------------------------------|
| Reverse polarity protection                                         |       | reverse polarity protected                                   |
| Short-circuit protection                                            |       | pulsing                                                      |
| Voltage drop                                                        | $U_d$ | $\leq 3 \text{ V}$                                           |
| Voltage drop at $I_L$                                               |       |                                                              |
| Voltage drop $I_L = 100 \text{ mA}$ , switching element on          | $U_d$ | $1.5 \dots 2.5 \text{ V typ. } 1.9 \text{ V}$                |
| Operating current                                                   | $I_L$ | $0 \dots 200 \text{ mA}$                                     |
| Lowest operating current                                            | $I_m$ | $0 \text{ mA}$                                               |
| Off-state current                                                   | $I_r$ | $0 \dots 0.5 \text{ mA typ. } 0.01 \text{ mA}$               |
| Off-state current $T_U = 40^\circ \text{C}$ , switching element off |       | $\leq 100 \mu\text{A}$                                       |
| No-load supply current                                              | $I_0$ | $\leq 9 \text{ mA}$                                          |
| Time delay before availability                                      | $t_v$ | $\leq 30 \text{ ms}$                                         |
| Switching state indicator                                           |       | LED, yellow                                                  |
| <b>Functional safety related parameters</b>                         |       |                                                              |
| MTTF <sub>d</sub>                                                   |       | 750 a                                                        |
| Mission Time ( $T_M$ )                                              |       | 20 a                                                         |
| Diagnostic Coverage (DC)                                            |       | 0 %                                                          |
| <b>Compliance with standards and directives</b>                     |       |                                                              |
| Standard conformity                                                 |       |                                                              |
| Standards                                                           |       | EN IEC 60947-5-2                                             |
| <b>Approvals and certificates</b>                                   |       |                                                              |
| UL approval                                                         |       | cULus Listed, General Purpose                                |
| CCC approval                                                        |       | Certified by China Compulsory Certification (CCC)            |
| <b>Ambient conditions</b>                                           |       |                                                              |
| Ambient temperature                                                 |       | $-25 \dots 70^\circ \text{C} (-13 \dots 158^\circ \text{F})$ |
| Storage temperature                                                 |       | $-40 \dots 85^\circ \text{C} (-40 \dots 185^\circ \text{F})$ |
| <b>Mechanical specifications</b>                                    |       |                                                              |
| Connection type                                                     |       | Connector plug                                               |
| Housing material                                                    |       | Stainless steel 1.4305 / AISI 303                            |
| Sensing face                                                        |       | PBT                                                          |
| Degree of protection                                                |       | IP67                                                         |
| Connector                                                           |       |                                                              |
| Threading                                                           |       | M12 x 1                                                      |
| Number of pins                                                      |       | 3                                                            |
| Dimensions                                                          |       |                                                              |
| Length                                                              |       | 65 mm                                                        |
| Diameter                                                            |       | 18 mm                                                        |

## Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 2 | WH | (white) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |

Release date: 2024-12-10 Date of issue: 2024-12-11 Filename: 282958\_eng.pdf