




## Inductive sensor NRB12-18GM40-E2-C-V1

- 12 mm quasi flush
- Reduction factor = 1
- Weld Immune
- Magnetic field resistant



### Dimensions



### Technical Data

#### General specifications

|                             |       |                    |
|-----------------------------|-------|--------------------|
| Switching function          |       | Normally open (NO) |
| Output type                 |       | PNP                |
| Rated operating distance    | $s_n$ | 12 mm              |
| Installation                |       | quasi flush        |
| Output polarity             |       | DC                 |
| Assured operating distance  | $s_a$ | 0 ... 9.72 mm      |
| Reduction factor $r_{Al}$   |       | 1                  |
| Reduction factor $r_{Cu}$   |       | 1                  |
| Reduction factor $r_{304}$  |       | 1                  |
| Reduction factor $r_{S137}$ |       | 1                  |
| Output type                 |       | 3-wire             |


#### Nominal ratings

|                   |       |                |
|-------------------|-------|----------------|
| Operating voltage | $U_B$ | 10 ... 30 V DC |
|-------------------|-------|----------------|


## Technical Data

|                                                 |           |                                                                    |
|-------------------------------------------------|-----------|--------------------------------------------------------------------|
| Switching frequency                             | f         | 0 ... 600 Hz                                                       |
| Hysteresis                                      | H         | typ. 3 %                                                           |
| Reverse polarity protection                     |           | reverse polarity protected                                         |
| Short-circuit protection                        |           | pulsing                                                            |
| Voltage drop                                    | $U_d$     | $\leq 3$ V                                                         |
| Operating current                               | $I_L$     | 0 ... 200 mA                                                       |
| Off-state current                               | $I_r$     | 0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C                             |
| No-load supply current                          | $I_0$     | $\leq 25$ mA                                                       |
| Switching state indicator                       |           | Multihole-LED, yellow                                              |
| Mag. Field strength, AC fields                  |           | 200 mT                                                             |
| Mag. Field strength, DC fields                  |           | 200 mT                                                             |
| <b>Functional safety related parameters</b>     |           |                                                                    |
| MTTF <sub>d</sub>                               |           | 1074 a                                                             |
| Mission Time (T <sub>M</sub> )                  |           | 20 a                                                               |
| Diagnostic Coverage (DC)                        |           | 0 %                                                                |
| <b>Compliance with standards and directives</b> |           |                                                                    |
| Standard conformity                             |           |                                                                    |
| Standards                                       |           | EN IEC 60947-5-2                                                   |
| <b>Approvals and certificates</b>               |           |                                                                    |
| Protection class                                |           | II                                                                 |
| Rated insulation voltage                        | $U_i$     | 60 V                                                               |
| Rated impulse withstand voltage                 | $U_{imp}$ | 800 V                                                              |
| UL approval                                     |           | cULus Listed, General Purpose                                      |
| CCC approval                                    |           | CCC approval / marking not required for products rated $\leq 36$ V |
| <b>Ambient conditions</b>                       |           |                                                                    |
| Ambient temperature                             |           | -25 ... 70 °C (-13 ... 158 °F)                                     |
| Storage temperature                             |           | -40 ... 85 °C (-40 ... 185 °F)                                     |
| <b>Mechanical specifications</b>                |           |                                                                    |
| Connection type                                 |           | Connector plug M12 x 1 , 4-pin                                     |
| Housing material                                |           | Brass, PTFE coated                                                 |
| Sensing face                                    |           | Ryton R4                                                           |
| Degree of protection                            |           | IP67                                                               |
| Dimensions                                      |           |                                                                    |
| Length                                          |           | 40 mm                                                              |
| Diameter                                        |           | 18 mm                                                              |

## Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 2 | WH | (white) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |

Release date: 2024-05-28 Date of issue: 2024-06-06 Filename: 201474\_eng.pdf