


Inductive ring sensor

RC10-14-N3-Y187455

- 10 mm inside diameter
- Comfort series



Dimensions



Technical Data

General specifications

Switching function	Normally closed (NC)
Output type	NAMUR, bistable
Inside diameter	10 mm
Measuring cone	4 mm, 1.4401
Passage speed	v ≤ 10 m/s
Output type	2-wire

Nominal ratings

Nominal voltage	U _o	8.2 V (R _i approx. 1 kΩ)
Operating voltage	U _B	5 ... 25 V
Hysteresis	H	typ. 1 %
Reverse polarity protection		reverse polarity protected
Current consumption		
Passage B U _B =8V		≥ 3 mA
Passage B U _B =10V		≥ 4.2 mA
Passage A U _B =10V		0.5 ... 1 mA typ. 0.9 mA
Passage A U _B =8V		0.5 ... 0.95 mA typ. 0.8 mA
Power ON		≥ 3 mA with U _B = 8 V ≥ 4.2 mA at U _B = 10
Time delay before availability	t _v	≤ 5 ms

Functional safety related parameters

MTTF _d	2130 a
Mission Time (T _M)	20 a
Diagnostic Coverage (DC)	0 %

Compliance with standards and directives

Standard conformity	
NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999

Release date: 2024-05-27 Date of issue: 2024-05-28 Filename: 187455_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Standards	EN IEC 60947-5-2
Approvals and certificates	
ATEX approval	
Equipment protection level Gb	PTB 99 ATEX 2128 X
UL approval	cULus Listed, General Purpose
Ambient conditions	
Ambient temperature	-25 ... 100 °C (-13 ... 212 °F)
Storage temperature	-40 ... 100 °C (-40 ... 212 °F)
Mechanical specifications	
Connection type	cable PVC , 2 m Crimp terminal sockets 60888-3, AMP
Core cross section	0.14 mm²
Housing material	PBT
Degree of protection	IP67
Cable	
Bending radius	> 10 x cable diameter
Mass	36 g
Dimensions	
Height	32.5 mm
Width	25 mm
Length	20 mm
General information	
Use in the hazardous area	see instruction manuals

Connection



Release date: 2024-05-27 Date of issue: 2024-05-28 Filename: 187455_eng.pdf