




## Triangulation sensor (BGE)

### OBT350-R101-EP-IO-0,3M-V3-1T



- Miniature design with versatile mounting options
- Secure and gapless detection, even near the surface through background evaluation
- Precision object detection, almost irrespective of the color
- Extended temperature range  
-40 °C ... 60 °C
- High degree of protection IP69K
- IO-Link interface for service and process data

Triangulation sensor with background evaluation




### Function

The miniature optical sensors are the first devices of their kind to offer an end-to-end solution in a small single standard design — from thru-beam sensor through to a distance measurement device. As a result of this design, the sensors are able to perform practically all standard automation tasks.

The DuraBeam laser sensors are durable and can be used in the same way as a standard sensor.

The use of Multi Pixel Technology gives the standard sensors a high level of flexibility and enables them to adapt more effectively to their operating environment.

### Dimensions



Release date: 2023-04-05 Date of issue: 2023-04-05 Filename: 267075-0101\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Technical Data


|                                             |                |                                                                                                                                                             |
|---------------------------------------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General specifications</b>               |                |                                                                                                                                                             |
| Detection range                             |                | 5 ... 350 mm                                                                                                                                                |
| Detection range min.                        |                | 5 ... 25 mm                                                                                                                                                 |
| Detection range max.                        |                | 5 ... 350 mm                                                                                                                                                |
| Adjustment range                            |                | 25 ... 350 mm                                                                                                                                               |
| Reference target                            |                | standard white, 100 mm x 100 mm                                                                                                                             |
| Light source                                |                | LED                                                                                                                                                         |
| Light type                                  |                | modulated visible red light                                                                                                                                 |
| LED risk group labelling                    |                | exempt group                                                                                                                                                |
| Black-white difference (6 %/90 %)           |                | < 15 % at 350 mm                                                                                                                                            |
| Diameter of the light spot                  |                | approx. 20 mm at a distance of 350 mm                                                                                                                       |
| Opening angle                               |                | approx. 3 °                                                                                                                                                 |
| Ambient light limit                         |                | EN 60947-5-2 : 40000 Lux                                                                                                                                    |
| <b>Functional safety related parameters</b> |                |                                                                                                                                                             |
| MTTF <sub>d</sub>                           |                | 600 a                                                                                                                                                       |
| Mission Time (T <sub>M</sub> )              |                | 20 a                                                                                                                                                        |
| Diagnostic Coverage (DC)                    |                | 0 %                                                                                                                                                         |
| <b>Indicators/operating means</b>           |                |                                                                                                                                                             |
| Operation indicator                         |                | LED green:<br>constantly on - power on<br>flashing (4Hz) - short circuit<br>flashing with short break (1 Hz) - IO-Link mode                                 |
| Function indicator                          |                | LED yellow:<br>constantly on - background detected (object not detected)<br>constantly off - object detected                                                |
| Control elements                            |                | Light-on/dark-on changeover switch                                                                                                                          |
| Control elements                            |                | Sensing range adjuster                                                                                                                                      |
| <b>Electrical specifications</b>            |                |                                                                                                                                                             |
| Operating voltage                           | U <sub>B</sub> | 10 ... 30 V DC                                                                                                                                              |
| Ripple                                      |                | max. 10 %                                                                                                                                                   |
| No-load supply current                      | I <sub>0</sub> | < 25 mA at 24 V supply voltage                                                                                                                              |
| Protection class                            |                | III                                                                                                                                                         |
| <b>Interface</b>                            |                |                                                                                                                                                             |
| Interface type                              |                | IO-Link ( via C/Q = pin 4 )                                                                                                                                 |
| IO-Link revision                            |                | 1.1                                                                                                                                                         |
| Device profile                              |                | Smart Sensor                                                                                                                                                |
| Device ID                                   |                | 0x110701 (1115905)                                                                                                                                          |
| Transfer rate                               |                | COM2 (38.4 kBit/s)                                                                                                                                          |
| Min. cycle time                             |                | 2.3 ms                                                                                                                                                      |
| Process data width                          |                | Process data input 1 Bit<br>Process data output 2 Bit                                                                                                       |
| SIO mode support                            |                | yes                                                                                                                                                         |
| Compatible master port type                 |                | A                                                                                                                                                           |
| <b>Output</b>                               |                |                                                                                                                                                             |
| Switching type                              |                | The switching type of the sensor is adjustable. The default setting is:<br>C/Q - Pin4: NPN normally open / dark-on, PNP normally closed / light-on, IO-Link |
| Signal output                               |                | 1 push-pull (4 in 1) output, short-circuit protected, reverse polarity protected, overvoltage protected                                                     |
| Switching voltage                           |                | max. 30 V DC                                                                                                                                                |
| Switching current                           |                | max. 100 mA , resistive load                                                                                                                                |
| Usage category                              |                | DC-12 and DC-13                                                                                                                                             |
| Voltage drop                                | U <sub>d</sub> | ≤ 1.5 V DC                                                                                                                                                  |
| Switching frequency                         | f              | 500 Hz                                                                                                                                                      |
| Response time                               |                | 1 ms                                                                                                                                                        |
| <b>Conformity</b>                           |                |                                                                                                                                                             |

Release date: 2023-04-05 Date of issue: 2023-04-05 Filename: 267075-0101\_eng.pdf

Technical Data

|                            |                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Communication interface    | IEC 61131-9                                                                                                                        |
| Product standard           | EN 60947-5-2                                                                                                                       |
| Approvals and certificates |                                                                                                                                    |
| UL approval                | E87056 , cULus Listed , class 2 power supply , type rating 1                                                                       |
| Ambient conditions         |                                                                                                                                    |
| Ambient temperature        | -40 ... 60 °C (-40 ... 140 °F) , fixed cable<br>-25 ... 60 °C (-13 ... 140 °F) , movable cable not appropriate for conveyor chains |
| Storage temperature        | -40 ... 70 °C (-40 ... 158 °F)                                                                                                     |
| Mechanical specifications  |                                                                                                                                    |
| Housing width              | 13.9 mm                                                                                                                            |
| Housing height             | 33.8 mm                                                                                                                            |
| Housing depth              | 18.3 mm                                                                                                                            |
| Degree of protection       | IP67 / IP69 / IP69K                                                                                                                |
| Connection                 | 300 mm fixed cable with M8 x 1, 3-pin connector                                                                                    |
| Material                   |                                                                                                                                    |
| Housing                    | PC (Polycarbonate)                                                                                                                 |
| Optical face               | PMMA                                                                                                                               |
| Mass                       | approx. 17 g                                                                                                                       |
| Cable length               | 0.3 m                                                                                                                              |

Connection



Connection Assignment




Wire colors in accordance with EN 60947-5-2


|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |

Release date: 2023-04-05 Date of issue: 2023-04-05 Filename: 267075-0101\_eng.pdf

Assembly



|   |                                    |
|---|------------------------------------|
| 1 | Light-on/dark-on changeover switch |
| 2 | Sensing range adjuster             |
| 3 | Operating indicator / dark on      |
| 4 | Signal indicator                   |
| 5 | Operating indicator / light on     |



Accessories

|  |                            |                                                                                |
|--|----------------------------|--------------------------------------------------------------------------------|
|  | <b>V31-GM-2M-PUR</b>       | Female cordset single-ended M8 straight A-coded, 4-pin, PUR cable grey         |
|  | <b>V31-WM-2M-PUR</b>       | Female cordset single-ended M8 angled A-coded, 4-pin, PUR cable grey           |
|  | <b>V3-WM-2M-PUR</b>        | Female cordset single-ended M8 angled A-coded, 3-pin, PUR cable grey           |
|  | <b>ICE2-8IOL-G65L-V1D</b>  | EtherNet/IP IO-Link master with 8 inputs/outputs                               |
|  | <b>ICE3-8IOL-G65L-V1D</b>  | PROFINET IO IO-Link master with 8 inputs/outputs                               |
|  | <b>ICE1-8IOL-G30L-V1D</b>  | Ethernet IO-Link module with 8 inputs/outputs                                  |
|  | <b>ICE1-8IOL-G60L-V1D</b>  | Ethernet IO-Link module with 8 inputs/outputs                                  |
|  | <b>ICE2-8IOL-K45P-RJ45</b> | EtherNet/IP IO-Link master with 8 inputs/outputs, DIN rail, push-in connectors |
|  | <b>ICE2-8IOL-K45S-RJ45</b> | EtherNet/IP IO-Link master with 8 inputs/outputs, DIN rail, screw terminal     |
|  | <b>ICE3-8IOL-K45P-RJ45</b> | PROFINET IO IO-Link master with 8 inputs/outputs, DIN rail, push-in terminals  |


Release date: 2023-04-05 Date of issue: 2023-04-05 Filename: 267075-0101\_eng.pdf

Accessories

|                                                                                   |                             |                                                                                                              |
|-----------------------------------------------------------------------------------|-----------------------------|--------------------------------------------------------------------------------------------------------------|
|  | <b>ICE3-8IOL-K45S-RJ45</b>  | PROFINET IO IO-Link master with 8 inputs/outputs, DIN rail, screw terminal                                   |
|  | <b>IO-Link-Master02-USB</b> | IO-Link master, supply via USB port or separate power supply, LED indicators, M12 plug for sensor connection |

Release date: 2023-04-05 Date of issue: 2023-04-05 Filename: 267075-0101\_eng.pdf

## Configuration



- 1 - Light on / dark on changeover switch
- 2 - Sensing range / sensitivity adjuster
- 3 - Operating indicator / dark on
- 4 - Signal indicator
- 5 - Operating indicator / light on

To unlock the adjustment functions turn the sensing range adjuster for more than 180 degrees.

### Sensing Range / Sensitivity

Turn sensing range / sensitivity adjuster clockwise to increase sensing range / sensitivity.

Turn sensing range / sensitivity adjuster counterclockwise to decrease sensing range / sensitivity.

If the end of the adjustment range is reached, the signal indicator starts flashing with 8 Hz.

### Light on / Dark on Configuration

Press the light on / dark on changeover switch for more than 1 second (less than 4 seconds). The light on / dark on mode changes and the operating indicators are activated accordingly.

If you press the light on / dark on changeover switch for more than 4 seconds, the light on / dark on mode changes back to the original setting. On release of the light on / dark on changeover switch the current state is activated.

### Restore Factory Settings

Press the light on / dark on changeover switch for more than 10 seconds (less than 30 seconds) until all LEDs turn off. On release of the light on / dark on changeover switch the signal indicator turns on. After 5 seconds the sensor resumes operation with factory settings.

After 5 minutes of inactivity the sensing range / sensitivity adjustment is locked. In order to reactivate the sensing range / sensitivity adjustment, turn the sensing range / sensitivity adjuster for more than 180 degrees.