



Mounting aid MH 04-2681F



- Suitable for VariKont, +U1+ and +U9* sensors
- Fixing screws for VariKont included in delivery

Mounting aid for VariKont, +U1+ and +U9*


Function

The mounting bracket type 04-2681 simplifies the adjustment of sensors of the model line VariKont® and the series +U1+ and +U9* according to DIN 43694, EN 50025 or EN 50037.

Fitting is simple using the well-tried and tested C section rail (e.g. NIEDAX GmbH) according to EN 50024 (15 mm x 30 mm x 1.5 mm). For existing installations, the mounting bracket is suitable for the C section rail according to the expiring DIN 43662 (15 mm x 30 mm x 2 mm). Instead of the C section rail, two-point fitting is possible. The respective drill holes are accessible via the middle guiding slot. Screws M5 x 16 mm can be used.

Large adjusting ranges in x and y direction and the 360° turning range simplify and reduce the mounting and adjustment work. The selected position can be adjusted by tightening the sensor mounting screws (included in the delivery package).

Dimensions



Technical Data

Standard conformity

Standards	IEC 68-2-6, IEC 68-2-27
-----------	-------------------------

Ambient conditions

Shock resistance	b < 30 g, T < 11 ms
Vibration resistance	f < 55 Hz, a < 1 mm

Mechanical specifications

Material	Chrome coated diecast zinc
Mass	approx. 270 g
Dimensions	90 mm x 40 mm x 28 mm (with 2-point fixing)

Release date: 2021-02-05 Date of issue: 2021-02-05 Filename: 033552_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS