


# Glass fiber optic

## LME 18-1,9-12,0-K4




- Sturdy metallic version
- Chemical-resistant
- M10 x 1 thread



Glass fiber optic - thru-beam with metal covering

### Dimensions



### Technical Data

#### General specifications

|                       |   |            |
|-----------------------|---|------------|
| Fiber optic length    | l | 12 m       |
| Fiber optic diameter  | d | 5 mm       |
| Adapter form          |   | 18         |
| End piece             |   | thread     |
| Bending radius        |   | min. 18 mm |
| Fiber bundle diameter |   | 1.9 mm     |
| Angle of divergence   |   | 68 °       |

#### Approvals and certificates

|           |    |
|-----------|----|
| Approvals | CE |
|-----------|----|

#### Ambient conditions

|                     |                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------|
| Ambient temperature | -20 ... 85 °C (-4 ... 185 °F) [Adapter]<br>-50 ... 260 °C (-58 ... 500 °F) [End head and Covering] |
| Storage temperature | -20 ... 85 °C (-4 ... 185 °F)                                                                      |

#### Mechanical specifications

|                      |      |
|----------------------|------|
| Degree of protection | IP40 |
| Material             |      |

Release date: 2021-07-07 Date of issue: 2021-07-07 Filename: 097908\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

**Technical Data**

|                               |                                   |
|-------------------------------|-----------------------------------|
| Optical face                  | glass                             |
| Sheathing                     | metal                             |
| Core                          | Glass fiber                       |
| End piece                     | Stainless steel 1.4305 / AISI 303 |
| Adapter                       | PBT                               |
| Extraction force              | at probe at 20°C: 120 N           |
| <b>Fiber optic amplifiers</b> |                                   |
| Device series                 | VL18LL<br>VariKont M              |

## Application

**Attention:**

Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.

