





Activator BT32XAS

- Two fixed operating surfaces offset by 180°
- Action reversed (end position undamped)
- Finger protection

Activator for F25 series

Dimensions



Technical Data

General specifications

Ring diameter	max. 40 mm
Spring ring height	max. 6 mm

Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Shaft diameter	< 31 mm
Shaft height	20 mm
Mounting hole pattern	30 x 80 mm
Material	
Housing	1.4057
Stopper cap	PBT (1 unit black)
Mounting screw	Stainless steel 1.4305 / AISI 303
Mass	200 g
Tightening torque, fastening screws	1.5 Nm

Release date: 2021-04-01 Date of issue: 2021-04-01 Filename: 212364_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**