



Metal protection hose CP-CDT-MS-5/16-10M

- Halogen-free
- 5/16" flexible metal conduit

5/16" flexible metal conduit 10 m

Function

The flexible metal conduit is used in conjunction with a suitable sensor adapter and a suitable cable gland to form a cable protection system for sensors. The purpose of this system is to protect the sensor wiring in harsh environments.

Dimensions



Technical Data

Ambient conditions

Ambient temperature	- 100 ... 600 °C (212 ... 1112 °F)
---------------------	------------------------------------

Mechanical specifications

Length	L	10 m
Bending radius		static 50 mm dynamic 60 mm
Degree of protection		IP40
Mech. capacity		
Impact resistance		Class 4, heavy (6 J) , according to EN-IEC 61386
Pressure resistance		Class 5, very heavy (4000 N) , according to EN-IEC 61386
Tensile strength		Class 4, heavy (1000 N) , according to EN-IEC 61386
Material		stainless steel 1.4301 / AISI 304

Technical Data

Mass	1720 g
General information	
Supplementary information	observe mounting instructions

Matching system components

	CP-ADP-MS-5/16-M18 5pcs	Sensor adapter for M18 sensors and 5/16" flexible metal conduit
	CP-ADP-MS-5/16-M30 5pcs	Sensor adapter for M30 sensors and 5/16" flexible metal conduit
	CP-CGL-MS-5/16-M16 5pcs	Cable gland M16 for cable diameter 4 ... 6.8 mm and 5/16" flexible metal conduit
	CP-CGL-MS-5/16-M20 5pcs	Cable gland M20 for cable diameter 4 ... 6.8 mm and 5/16" flexible metal conduit
	CG.CO.M16S.BN. C.16.K01	