



Model Number

KHR-C02-1,3-2,0-K92

Plastic fiber optic - diffuse

Threading M4

Features

- High flexible
- Thread M4

Description

Attention:

Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.



Accessories

OMH-LL-M4

Mounting bracket for fiber optic cable, M4 thread

KM4-0,5

Metal protection for plastic fiber optics
M4 x 0.5 m

KM4-1,0

Metal protection for plastic fiber optics
M4 x 1.0 m

Technical data

General specifications

Sensor range		SU18: 60 mm SU18/35: 210 mm SU19: 60 mm
Fiber optic length	l	2000 mm , adjustable
Fiber optic diameter	d	1.3 mm
Adapter form		00
End piece		thread
Bending radius		min. 2 mm
Fiber configuration	Fv	see dimensions
Angle of divergence		67 °
Accessories provided		Cutter for plastic fiber optics

Ambient conditions

Ambient temperature	-40 ... 70 °C (-40 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Material	
Optical face	plastic
Sheathing	PVC
Core	plastic
End piece	Stainless steel 1.4305 / AISI 303

Dimensions

