

REI-10S6S-2B150-H1181
Incremental Encoder
Industrial Line



Features

- Synchro flange, Ø 58 mm
- Solid shaft, Ø 6 mm × 10 mm
- Optical measuring principle
- Shaft material: stainless steel
- Protection class IP67 on housing and shaft side
- -40...+85 °C
- Max. 6000 rpm (continuous operation 3000 rpm)
- 10...30 VDC
- Push-pull/HTL invertible
- Pulse frequency max. 300 kHz
- M12 × 1 male connector, 8-pin
- 150 pulses per revolution

Technical data

Type	REI-10S6S-2B150-H1181
ID	100046088
Measuring principle	Optical
General data	
Max. Rotational Speed	6000 rpm
Moment of inertia of the rotor	1.8 × 10 ⁻⁵ kgm ²
Starting torque	< 0.05 Nm
Output type	Incremental
Resolution incremental	150 ppr
Electrical data	
Operating voltage U _B	10...30 VDC
No-load current	≤ 100 mA
Output current	≤ 30 mA
Short-circuit protection	yes
Wire break/reverse polarity protection	yes
Pulse frequency max.	300 kHz
Signal level high	min. U _B - 1 V
Signal level low	max. 0.5 V
Output function	Push-Pull/HTL, invertable
Mechanical data	
Flange type	Synchro flange
Flange diameter	Ø 58 mm
Shaft Type	Solid shaft
Shaft diameter D (mm)	6
Shaft Length L [mm]	10
Shaft material	Stainless steel

Wiring diagram




Technical data

Housing material	Die-cast zinc
Electrical connection	Connector, M12 × 1
	8-pin
Axial shaft load	40 N
Radial shaft load	80 N
Environmental conditions	
Ambient temperature	-40...+85 °C
Vibration resistance (EN 60068-2-6)	300 m/s², 10...2000 Hz
Shock resistance (EN 60068-2-27)	3000 m/s², 6 ms
Protection class	IP67
Protection class shaft	IP67

Accessories


RCS-15-08-06 1545361

Bellows coupling, outer diameter:
15 mm, bore diameter: 8 mm/6 mm




RCS-15-06-04 1545363

Bellows coupling, outer diameter:
15 mm, bore diameter: 6 mm/4 mm




RA-BC-20-06-06 100048777

Bellows coupling with aluminum hub
Ø 20 mm; d1 = 6 mm, d2 = 6 mm




RA-BC-20-06-08 100048778

Bellows coupling with aluminum hub
Ø 20 mm; d1 = 6 mm, d2 = 8 mm




RA-BC-20-06-10 100048779

Bellows coupling with aluminum hub
Ø 20 mm; d1 = 6 mm, d2 = 10 mm




RA-BC-E-20-06-06 100048785

Stainless steel bellows coupling Ø
20 mm; d1 = 6 mm, d2 = 6 mm




RA-BC-E-20-06-10 100048786

Stainless steel bellows coupling Ø
20 mm; d1 = 6 mm, d2 = 10 mm




RA-SDC-30-06-10 100048791

Spring disc coupling Ø 30 mm; d1 =
6 mm, d2 = 10 mm




RA-SDC-30-06-06 100048790

Spring disc coupling Ø 30 mm; d1 =
6 mm, d2 = 6 mm




RA-HC-25-06-06 100048794

Aluminum helix coupling Ø 25 mm; d1 =
6 mm, d2 = 6 mm



RA-HC-25-06-10

100048795



Accessories

Dimension drawing	Type	ID	
RKC8T-2/TXL		6625142	Connection cable, M12 female connector, straight, 8-pin, cable length: 2 m, jacket material: PUR, black; cULus approval
WKC8T-2/TXL		6625145	Connection cable, M12 female connector, angled, 8-pin, cable length: 2 m, jacket material: PUR, black; cULus approval