


REI-43H38S-4C1024-H1181  
Incremental Encoder  
Industrial Line





Technical data

|                                        |                                         |
|----------------------------------------|-----------------------------------------|
| Type                                   | REI-43H38S-4C1024-H1181                 |
| ID                                     | 100011448                               |
| Measuring principle                    | Optical                                 |
| General data                           |                                         |
| Max. Rotational Speed                  | 6000 rpm                                |
| Moment of inertia of the rotor         | 220 × 10 <sup>-6</sup> kgm <sup>2</sup> |
| Starting torque                        | < 0.2 Nm                                |
| Output type                            | Incremental                             |
| Resolution incremental                 | 1024 ppr                                |
| Electrical data                        |                                         |
| Operating voltage U <sub>B</sub>       | 10...30 VDC                             |
| No-load current                        | ≤ 120 mA                                |
| Output current                         | ≤ 20 mA                                 |
| Short-circuit protection               | yes                                     |
| Wire break/reverse polarity protection | yes                                     |
| Pulse frequency max.                   | 300 kHz                                 |
| Signal level high                      | min. 2.5 V                              |
| Signal level low                       | max. 0.5 V                              |
| Output function                        | 8-wire, RS422/TTL, invertable           |
| Mechanical data                        |                                         |
| Flange type                            | Flange without mounting element         |
| Flange diameter                        | Ø 100 mm                                |
| Shaft Type                             | Blind hole shaft                        |
| Shaft diameter D (mm)                  | 38                                      |
| Shaft diameter D                       | 1.496 in                                |
| Shaft material                         | Stainless steel                         |

Features

- Flange without mounting element, Ø 100 mm
- Hollow shaft, Ø 38 mm
- Optical measuring principle
- Shaft material: stainless steel
- Protection class IP65 on the shaft side
- -40...+80 °C
- Max. 6000 rpm
- 10...30 VDC
- RS422/TTL invertible
- Pulse frequency max. 300 kHz
- M12 × 1 male connector, 8-pin
- 1024 pulses per revolution



Technical data

|                                     |                               |
|-------------------------------------|-------------------------------|
| Housing material                    | Die-cast zinc                 |
| Electrical connection               | Connector, M12 × 1            |
|                                     | 8-pin                         |
| Axial shaft load                    | 100 N                         |
| Radial shaft load                   | 200 N                         |
| Environmental conditions            |                               |
| Ambient temperature                 | -40...+80 °C                  |
| Vibration resistance (EN 60068-2-6) | 10 g (100 m/s²), 10...2000 Hz |
| Shock resistance (EN 60068-2-27)    | 200 g (2000 m/s²), 6 ms       |
| Protection class                    | IP65                          |
| Protection class shaft              | IP65                          |

Accessories

RSA-7 1544808

Inlay, outer diameter 38 mm, inner diameter 12 mm

RSA-11 1545469


Inlay, outer diameter 38 mm, inner diameter 16 mm

RSA-10 1545465

Inlay, outer diameter 38 mm, inner diameter 25 mm


RME-5 1544616

Stainless steel mounting panel for hollow shaft encoders, reference diameter 149 mm, for applications with axial play




RME-6 1544617

Stainless steel mounting panel for hollow shaft encoders, reference diameter 104...206 mm, for applications with fixing points on adjustable reference diameter




RME-10 1544621

Stainless steel mounting element for hollow shaft encoders, pitch diameter 110 mm, for applications with high axial play



RME-11 1544622

Stainless steel mounting element for hollow shaft encoders, pitch diameter 76 mm, for applications with limited mounting space



RME-15 1544626

Metal arm bracket, for hollow shaft encoders, length 70 mm; for applications with little axial and radial play; flexibly adjustable

