


Technical data


	5-pin
Axial shaft load	40 N
Radial shaft load	80 N
Environmental conditions	
Ambient temperature	-20...+70 °C
Vibration resistance (EN 60068-2-6)	30 g (300 m/s ²), 10...2000 Hz
Shock resistance (EN 60068-2-27)	500 g (2500 m/s ²), 4 ms
Protection class	IP64
Protection class shaft	IP64
MTTF	25 years

Accessories


RCS-15-08-06	1545361
Bellows coupling, outer diameter: 15 mm, bore diameter: 8 mm/6 mm	




RCS-15-06-06	1545362
Bellows coupling, outer diameter: 15 mm, bore diameter: 6 mm/6 mm	




RA-BC-20-06-06	100048777
Bellows coupling with aluminum hub Ø 20 mm; d1 = 6 mm, d2 = 6 mm	




RA-BC-20-06-08	100048778
Bellows coupling with aluminum hub Ø 20 mm; d1 = 6 mm, d2 = 8 mm	




RA-BC-20-06-10	100048779
Bellows coupling with aluminum hub Ø 20 mm; d1 = 6 mm, d2 = 10 mm	




RA-BC-E-20-06-06	100048785
Stainless steel bellows coupling Ø 20 mm; d1 = 6 mm, d2 = 6 mm	




RA-BC-E-20-06-10	100048786
Stainless steel bellows coupling Ø 20 mm; d1 = 6 mm, d2 = 10 mm	




RA-SDC-30-06-10	100048791
Spring disc coupling Ø 30 mm; d1 = 6 mm, d2 = 10 mm	



RA-SDC-30-06-06	100048790
Spring disc coupling Ø 30 mm; d1 = 6 mm, d2 = 6 mm	




RA-HC-25-06-06	100048794
Aluminum helix coupling Ø 25 mm; d1 = 6 mm, d2 = 6 mm	



RA-HC-25-06-10

100048795



Aluminum helix coupling Ø 25 mm; d1
= 6 mm, d2 = 10 mm