


BT26SM8

Glass Fiber – Bifurcated Fiber



Features

- Operating mode: Diffuse/Retroreflective
- Stainless steel jacket, flexible
- Operating temperature of fiber-optic jacket: -140...+249 °C
- End sleeve for sensor: Stainless steel, M8 thread
- Operating temperature of fiber-optic tip: -140...+249 °C
- Optical fiber, bundle diameter: 3.2 mm
- Optical fiber, total length: ± 1829 mm

Functional principle

Glass or plastic fibers are the optimum choice for high-temperature applications and limited spaces. They transfer the light from the sensor to a remote object. Individual fibers are used for opposed mode sensing, whereas bifurcated fibers are suited for retroreflective or diffuse mode operation.

Technical data

Type	BT26SM8
ID	3020009
Optical data	
Function	Diffuse mode sensor
Fiber-optic type	Glass
Mechanical data	
Dimensions	1828 mm
Housing material	Stainless steel
Jacket material	Stainless-steel mono-winding coil
Jacket material	metal, 1.4310 (AISI 301)
Bundle diameter	3.2 mm
Material of the fiber-optic tip	Stainless Steel
Bending radius	Ø 25 mm
Ambient temperature	-140...+249 °C
Max. temperature tip	249 °C
Protection class	IP67