

T30SP6FF600QP


Photoelectric Sensor – Diffuse Mode Sensor with Fixed-Field Background Suppression



Features

- Cable with male end M12 × 1, 4-pin, 150 mm
- Protection classes IP67/IP69K
- Ambient temperature: -40 °C...+70 °C
- Operating voltage: 10...30 VDC
- PNP switching output, changeover

Wiring diagram




Functional principle

The emitter and receiver are incorporated in a single housing. The light reflection of the target is detected and triggers the sensor to switch. Thus the switching distance largely depends on the reflectivity of the target.

Excess gain curve

Excess gain in relation to the distance



Technical data

Type	T30SP6FF600QP
ID	3018356
Optical data	
Function	Proximity switch
Operating mode	Background suppression, non-adjustable
Light type	IR
Wavelength	880 nm
Range	0...600 mm
Electrical data	
Operating voltage	10...30 VDC
No-load current	≤ 25 mA
Short-circuit protection	yes / Cyclic
Reverse polarity protection	yes
Output function	Connection programmable, PNP
Switching frequency	≤ 160 Hz
Readiness delay	≤ 100 ms
Response time typical	< 3 ms
Overcurrent release	> 220 mA
Mechanical data	
Design	Tube, T30
Dimensions	Ø 30 x 45 x 40 mm
Housing material	Plastic, Thermoplastic material
Lens	plastic, Acrylic
Electrical connection	Connector, M12 × 1, PVC
Number of cores	4
Ambient temperature	-40...+70 °C

Technical data

Protection class	IP69
Special features	Encapsulated Wash down
Power-on indication	LED, Green
Switching state	LED, Yellow
Error indication	LED, green, Flashing
Excess gain indication	LED
Alarm display	LED yellow Flashing
Tests/approvals	
MTTF	448 years acc. to SN 29500 (Ed. 99) 40 °C
Approvals	CE, UL, CSA

Accessories

SMB1815SF3053279

Mounting bracket, PBT black, for PICO-GUARD points

Technical drawing of SMB1815SF mounting bracket. Dimensions: 11,7, 50,8, 43,2, 25,4, 36,1, 15, 5.

SMB30A3032723

Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread

Technical drawing of SMB30A mounting bracket. Dimensions: 45, 61, 38,5, 69, 7,5, R 40, 6,3 wide, 30,5, 6,3.

SMB30FAM103011185

Mounting bracket, stainless steel, for M10 x 1.5 thread, thread length 30 mm

Technical drawing of SMB30FAM10 mounting bracket. Dimensions: 78,4, 60,3, 19, 30,1, 75, 61,6, 48, M10.

SMBAMS30P3073135

Mounting bracket, stainless steel, for sensors with 30 mm thread

Technical drawing of SMBAMS30P mounting bracket. Dimensions: 45, 93, 70,5, 22,5, 31, 25, 7, 6,5.