

# PT-30HG-1003-U1-H1143/S1800



## Pressure Transmitter – With Voltage Output (3-Wire)



### Features

- Ceramic measuring cell
- Compact and robust design
- Excellent EMC properties
- Pressure range -30...0 "Hg rel.
- 12...33 VDC
- Inverted analog output 10...0 V
- Process connection 1/4"-18 NPT male thread
- Plug-in device, M12 × 1

### Wiring diagram



### Technical data

|                                           |                                                                                                                                                                     |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                                      | PT-30HG-1003-U1-H1143/S1800                                                                                                                                         |
| ID                                        | 100049551                                                                                                                                                           |
| Special version                           | S1800 Corresponds to: PT pressure transmitter with inverted output. Example: Standard: 4 mA=0 psi and 20 mA=145 psi. Inverted output: 4 mA=145 psi and 20 mA=0 psi= |
| Pressure type                             | Relative pressure                                                                                                                                                   |
| Pressure range                            | -1.016...0 bar                                                                                                                                                      |
|                                           | -14.74...0 psi                                                                                                                                                      |
|                                           | -0.1...0 MPa                                                                                                                                                        |
| Admissible overpressure                   | ≤ 3 bar                                                                                                                                                             |
| Burst pressure                            | ≥ 3 bar                                                                                                                                                             |
| Response time                             | < 2 ms, typ. 1 ms                                                                                                                                                   |
| Long-term stability                       | 0.25 % FS, according to IEC EN 60770-1                                                                                                                              |
| <b>Power supply</b>                       |                                                                                                                                                                     |
| Operating voltage $U_B$                   | 12...33 VDC                                                                                                                                                         |
| Current consumption                       | ≤ 7 mA                                                                                                                                                              |
| Short-circuit/reverse polarity protection | yes / yes                                                                                                                                                           |
| Protection class                          | IP67                                                                                                                                                                |
| Insulation class                          | III                                                                                                                                                                 |
| Insulation voltage                        | 750 VDC                                                                                                                                                             |
| <b>Outputs</b>                            |                                                                                                                                                                     |
| Output 1                                  | Analog output                                                                                                                                                       |
| Output function                           | Analog output voltage                                                                                                                                               |
| <b>Analog output</b>                      |                                                                                                                                                                     |
| Voltage output                            | 10...0 V                                                                                                                                                            |
| Load                                      | ≤ 100 nF / >10 kΩ                                                                                                                                                   |

### Functional principle

The pressure sensors in the PT...-1000 product series operate with a ceramic measuring cell in various pressure ranges of up to -1...60 bar in 2-, 3- or even 4-wire technology. Depending on the sensor variant, the processed signal is available as an analog output signal (4...20 mA, 0...10 V, 0...5 V, 1...6 V, ratiometric) or as a digital IO-Link process parameter. The IO-Link sensor variants also have two independently configurable switching outputs.

In addition to the standard variants, there are special sensors for uses such as ATEX areas or for oxygen applications.

A wide range of process connections and electrical connections offer a high degree of flexibility in a wide range of applications.

## Technical data

|                                                 |                                                                                                                                     |
|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Resolution                                      | <± 0.1 % FS                                                                                                                         |
| <b>Temperature behaviour</b>                    |                                                                                                                                     |
| Medium temperature                              | -40...+135 °C                                                                                                                       |
| Temperature coefficient                         | ± 0.2 % of full scale/10 K                                                                                                          |
| <b>Environmental conditions</b>                 |                                                                                                                                     |
| Ambient temperature                             | -30...+85 °C                                                                                                                        |
| Storage temperature                             | -50...+100 °C                                                                                                                       |
| Vibration resistance                            | 20 g, 15...2000 Hz, 15...25 Hz with amplitude ± 15 mm, 1 octave/minute in all 3 directions, 50 continuous loads, acc. to IEC 68-2-6 |
| Shock resistance                                | 100 g, 11 ms, half sinusoidal curve, all 6 directions, free fall from 1 m onto concrete (6x) acc. to IEC 68-2-27                    |
| <b>Mechanical data</b>                          |                                                                                                                                     |
| Housing material                                | Stainless-steel/Plastic, 1.4404 (AISI 316L)/polyarylamide 50 % GF UL 94 V-0                                                         |
| Pressure connection material                    | Stainless steel 1.4404 (AISI 316L)                                                                                                  |
| Material pressure transducer                    | Ceramic Al <sub>2</sub> O <sub>3</sub>                                                                                              |
| Process connection                              | 1/4" NPT-18 male thread                                                                                                             |
| Wrench size pressure connection / coupling nut  | 24                                                                                                                                  |
| Electrical connection                           | Connector, M12 × 1                                                                                                                  |
| Max. tightening torque of housing nut           | 20 Nm                                                                                                                               |
| <b>Reference conditions acc. to IEC 61298-1</b> |                                                                                                                                     |
| Temperature                                     | 15...+25 °C                                                                                                                         |
| Atmospheric pressure                            | 860...1060 hPa abs.                                                                                                                 |
| Humidity                                        | 45...75 % rel.                                                                                                                      |
| Auxiliary power                                 | 24 VDC                                                                                                                              |
| <b>Tests/approvals</b>                          |                                                                                                                                     |
| Approvals                                       | cULus                                                                                                                               |
| UL registration number                          | E302799                                                                                                                             |
| MTTF                                            | 1238 years acc. to SN 29500 (Ed. 99) 40 °C                                                                                          |